



PySCeS

Python Simulator for Cellular Systems

PySCeS User Guide

Release 0.9.3

Brett Olivier, Johann Rohwer, Jannie Hofmeyr

March 22, 2016

I	Introduction	1
II	Getting started	5
1	Loading PySCeS	7
2	Creating a PySCeS model object	9
2.1	Advanced	9
3	Creating a PySCeS model object	11
4	Basic model attributes	13
4.1	Advanced	14
III	Modelling	15
5	Structural Analysis	17
5.1	Structural Analysis - new objects	17
5.2	Structural Analysis - legacy	18
6	Time simulation	19
6.1	Simulation results	20
6.2	Advanced	21
7	Steady-state analysis	23
7.1	New: mod.data_sstate	24
7.2	Stability	24
8	Metabolic Control Analysis	25
8.1	Elasticities	25
8.2	Control coefficients	25
8.3	Response coefficients	26
8.4	Response coefficients with respect to moiety-conserved sums	26

IV	Parameter scanning	29
9	Single dimension parameter scans	31
10	Two dimension parameter scans	33
11	Multi-dimension parameter scans	35
V	Plotting	37
VI	Displaying data	43
12	Displaying/saving model attributes	45
13	Writing formatted arrays	47
13.1	Write_array()	47
13.2	Write_array_latex()	48
VII	Installing and configuring	49
14	Configuring	53
VIII	References	55
IX	The PySCeS Model Description Language	57
15	Defining a PySCeS model	61
15.1	A kinetic model	61
15.2	Model keywords	61
15.3	Global unit definition	62
15.4	Symbol names and comments	62
15.5	Compartment definition	63
15.6	Function definitions	63
15.7	Defining fixed species	64
15.8	Reaction stoichiometry and rate equations	64
15.9	Species and parameter initialisation	66
16	Advanced model construction	69
16.1	Assignment rules	69
16.2	Rate rules	69
16.3	Events	70
16.4	Piecewise	70
16.5	Reagent placeholder	71
17	Example PySCeS input files	73

17.1	Basic model definition	73
17.2	Advanced example	74
X	PySCeS Module documentation	77
18	PyscesUtils	79
19	PyscesPlot2	83
20	PyscesModel	95
21	PyscesScan	119
22	PyscesInterfaces	123
23	PyscesStoich	125
24	PyscesLink	131
XI	Indices and tables	133
	Python Module Index	137
	Index	139

Part I

Introduction

PySCeS: the Python Simulator for Cellular Systems is an extendable toolkit for the analysis and investigation of cellular systems. It is available for download at <http://pysces.sourceforge.net>

Welcome! This users guide will get you started with the basics of modelling cellular systems with PySCeS. It is meant to be used together with the *input file guide*. If you already have PySCeS installed continue straight on if not, *Installing and configuring* contains instructions on building and installing PySCeS.

PySCeS is distributed under the PySCeS (BSD style) license and is made freely available as Open Source software. See LICENCE.txt for details.

PySCeS continued development depends, to a large degree on support and feedback from Systems Biology community, if you use PySCeS in your work please cite it using the following reference:

Brett G. Olivier, Johann M. Rohwer and Jan-Hendrik S. Hofmeyr *Modelling cellular systems with PySCeS*, Bioinformatics, 21, 560-561, DOI 10.1093/bioinformatics/bti046.

We hope that you will enjoy using our software. If, however, you find any unexpected features (i.e. bugs) or have any suggestions on how we can improve PySCeS please let us know.

The PySCeS development team.

Part II

Getting started

LOADING PYSCES

In this section we assume you have PySCeS installed and configured (see *Installing and configuring* for details) and a correctly formatted PySCeS input file that describes a cellular system in terms of its reactions, species and parameters. For a detailed description of the PySCeS Model Description Language see the *PySCeS Input File Guide*. Note that on all platforms PySCeS model files have the extension `.psc`.

To begin modelling we need to start up an interactive Python shell (we suggest `iPython`) and load PySCeS with `import pysces`:

```
Python 2.7.11 |Anaconda 2.4.1 (64-bit)| (default, Dec 7 2015, 14:10:42) [MSC v.
Type "copyright", "credits" or "license" for more information.

In [1]: import pysces
Matplotlib backend set to: "TkAgg"
Matplotlib interface loaded (pysces.plt.m)
Continuation routines available
NLEQ2 routines available
You are using NumPy (1.10.1) with SciPy (0.16.0)
RateChar is available
Parallel scanner is available

PySCeS environment
*****
pysces.model_dir = d:\\mypysces\\pscmmodels
pysces.output_dir = c:\\Pysces

*****
* Welcome to PySCeS (0.9.3) - Python Simulator for Cellular Systems *
*           http://pysces.sourceforge.net                       *
* Copyright(C) B.G. Olivier, J.M. Rohwer, J.-H.S. Hofmeyr, 2004-2016 *
* Triple-J Group for Molecular Cell Physiology                  *
* Stellenbosch University, ZA and VU University Amsterdam, NL  *
* PySCeS is distributed under the PySCeS (BSD style) licence, see *
* LICENCE.txt (supplied with this release) for details         *
*****
```

PySCeS is now ready to use. If you would like to test your installation try running the test suite:

```
pysces.test()
```

this also copies the test models supplied with PySCeS into your model directory.

CREATING A PYSCES MODEL OBJECT

This guide uses the test models supplied with PySCeS as examples, if you would like to use them and have not already done so run the PySCeS tests (described in the previous section).

Before modelling, a PySCeS model object needs to be instantiated. As a convention we use `mod` as the instantiated model instance. The following code creates such an instance using the test input file, `pysces_test_linear1.psc`:

```
>>> mod = pysces.model('pysces_test_linear1')

Assuming extension is .psc
Using model directory: C:\mypysces\pscmodels
C:\mypysces\pscmodels\pysces_test_linear1.psc loading .....

Parsing file: C:\mypysces\pscmodels\pysces_test_linear1.psc
Calculating L matrix . . . . . done.
Calculating K matrix . . . . . done.
```

When instantiating a new model object, PySCeS input files are assumed to have a `.psc` extension. If the specified input file does not exist in the input file directory (e.g. misspelled filename) a list of existing input files is shown and the user is given an opportunity to enter the correct filename.

2.1 Advanced

The model constructor can also be used to specify a model directory other than the default model path:

```
mod = pysces.model('pysces_test_linear1', dir='c:\\Pysces\\psc')
```

alternatively input files can also be loaded from a string:

```
>>> F = file('c:\\Pysces\\psc\\pysces_test_linear1.psc', 'r')
>>> pscS = F.read()
>>> F.close()
>>> mod = pysces.model('test_lin1s', loader='string', fString=pscS)
```

```
Assuming extension is .psc  
Using model directory: C:\mypysces\pscmmodels  
Using file: test_lin1s.psc  
C:\mypysces\pscmmodels\orca\test_lin1s.psc loading .....
```

note that now the input file is saved and loaded as model_dir\orca\test_lin1s.psc.

CREATING A PYSCES MODEL OBJECT

Once a new model object has been created it needs to be loaded. During the load process the input file is parsed, the model description is translated into Python data structures and a stoichiometric structural analysis is performed:

```
**New** in PySCeS 0.7.1+ model loading is now automatically performed when the model object is instantiated. This behaviour is controlled by the *autoload* argument (default = True). To keep backwards compatibility with older modelling scripts the first time doLoad() is called a warning is generated. Subsequent calls to doLoad() will reload the model as required
```

Once loaded, all the model elements contained in the input file are made available as model (`mod`) attributes so that in the input file where you might find initialisations such as `s1 = 1.0` and `k1 = 10.0` these are now available as `mod.s1` and `mod.k1`. For variable species and compartments an additional attribute is created which contains the elements *initial* (as opposed to *current*) value. These are constructed as `<name>*_init*`:

```
>>> mod.s1
1.0
>>> mod.s1_init
1.0
>>> mod.k1
10.0
```

Any errors generated during the loading process (almost always) occur as a result of syntax errors in the input file. These error messages may not be intuitive for example, ‘list out of range’ exception usually indicates a missing multiplication operator “3(” instead of “3*(” or unbalanced parentheses.

BASIC MODEL ATTRIBUTES

Some basic model properties are accessible once the model is loaded:

- `mod.ModelFile`, the name of the model file that was used.
- `mod.ModelDir`, the input file directory.
- `mod.ModelOutput`, the PySCeS work/output directory.
- Parameters are available as attributes directly as specified in the input file e.g. `k1` is `mod.k1`.
- External (fixed) species are made available in the same way.
- Internal (variable) species are treated in a similar way except that an additional attribute (parameter) is created to hold the species initial value (as specified in the input file), e.g., from `s1`, `mod.s1` and `mod.s1_init` are instantiated as model object attributes.
- Compartments are also assigned an initial value.
- Rate equations are translated into objects that return their current value when called `mod.R1()`.

All basic model attributes that are described here can be changed interactively. However, if the model rate equations need to be changed, this should be done in the input file after which the model should be re-instantiated and reloaded.

Groups of model properties (either tuples, lists or dictionaries)

- `mod.species` the model's variable species names (ordered relative to the stoichiometric matrix rows).
- `mod.reactions` reaction names and ordered to the stoichiometric matrices columns.
- `mod.parameters` all parameters (including fixed species)
- `mod.fixed_species` only the fixed species names
- `mod.__rate_rules__` a list of rate rules defined in the model

4.1 Advanced

These attributes are used by PySCeS to store additional information about the basic model components, generally they are supplied by the parser and should almost never be changed directly.

- `mod.__events__` a list of event object references which can be interrogated for event information. For example if you want a list of event names try `[ev.name for ev in mod.__events__]`
- `mod.__rules__` a dictionary containing information about all rules defined for this model
- `mod.__sDict__` a dictionary of species information
- `mod.__compartments__` a dictionary containing compartment information

Part III

Modelling

STRUCTURAL ANALYSIS

As part of the model loading procedure, `doLoad()` automatically performs a stoichiometric (structural) analysis of the model. The structural properties of the model are captured in stoichiometric matrix (**N**), kernel matrix (**K**) and link matrix (**L**). These matrices can either be displayed with a `mod.showX()` method or used in further calculations as numeric arrays. The formal definition of these matrices, as they are used in PySCeS, is described in ¹.

The structural properties of a model are available in two forms, as new-style objects which have all the array properties neatly encapsulated or as legacy attributes. Although both exist it is highly recommended to use the new objects.

5.1 Structural Analysis - new objects

For alternate descriptions of these model properties see the next (legacy) section.

- `mod.Nmatrix` view with `mod.showN()`
- `mod.Nrmatrix` view with `mod.showNr()`
- `mod.Lmatrix` view with `mod.showK()`
- `mod.L0matrix`
- `mod.Kmatrix` view with `mod.showL()`
- `mod.K0matrix`
- `mod.showConserved()` displays any moiety conserved relationships (if present).
- `mod.showFluxRelationships()` shows the relationships between dependent and independent fluxes at steady state.

All new structural objects have an *array* attribute which holds the actual NumPy array data as well as *ridx* and *cidx* which hold the row and column indexes (relative to the stoichiometric matrix) as well as the following methods:

- `.getLabels()` return the matrix labels as tuple([rows], [columns])
- `.getColsByName()` extract column(s) with label

¹ Hofmeyr, J.-H.S. (2001) *Metabolic control analysis in a nutshell*, in T.-M. Yi, M. Hucka, M. Morohashi, and H. Kitano, eds, Proceedings of the 2nd International Conference on Systems Biology, pp. 291-300.

- `.getRowsByName()` extract row(s) with label
- `.getIndexes()` return the matrix indices (relative to the Stoichiometric matrix) as tuple((rows), (columns))
- `.getColsByIdx()` extract column(s) referenced by index
- `.getRowsByIdx()` extract row(s) referenced by index

5.2 Structural Analysis - legacy

- `mod.nmatrix`, **N**: displayed with `mod.showN()`
- `mod.kmatrix`, **K**: displayed with `mod.showK()`
- `mod.lmatrix`, **L**: displayed with `mod.showL()` (an identity matrix means **L** does not exist i.e. no linear dependence).
- If there are linear dependencies in the differential equations then the reduced stoichiometric matrix of linearly independent, differential equations **Nr** is available as `mod.nrmatrix` and is displayed with `mod.showNr()`. If there is no dependence **Nr** = **N**.
- In the case where there is linear dependence the moiety conservation sums can be displayed by using `mod.showConserved()`. The conservation totals are calculated from the initial values of the variable species as defined in the model file.
- When the **K** and **L** matrices exist, their dependent parts (**K0**, **L0**) are available as `mod.kzeromatrix` and `mod.lzeromatrix`.
- `mod.showConserved()` prints any moiety conserved relationships (if present).
- `mod.showFluxRelationships()` shows the relationships between dependent and independent fluxes at steady state.

If the `mod.showX()` methods are used the row and column titles of the various matrices are displayed with the matrix. Additionally, all of the `mod.showX()` methods accept an open file object as an argument. If this file argument is present the method's results are output to a file and not printed to the screen. Alternatively, the order of each matrix dimension, relative to the stoichiometric matrix, is available as either a row or column array (e.g., `mod.krow`, `mod.lrow`, `mod.kzerocol`).

TIME SIMULATION

PySCeS has interfaces to two ODE solvers either LSODA from ODEPACK (part of SciPy) or SUNDIALS CVODE (using PySundials). If PySundials is installed it will automatically select CVODE if compartments, events or rate rules are detected during model load as LSODA is not able capable of event handling or changing compartment sizes. If, however, you would like to select the solver manually this is also possible:

```
mod.mode_integrator = 'LSODA'  
mod.mode_integrator = 'CVODE'
```

There are three ways of running a simulation:

1. Defining the *start*, *end* time and number of *points* and using the `mod.Simulate()` method directly:

```
mod.sim_start = 0.0  
mod.sim_end = 20  
mod.sim_points = 50  
mod.Simulate()
```

2. Using the `mod.doSim()` method where only the *end* time and *points* need to be specified. For example running a 20 point simulation from time 0 to 10:

```
>>> mod.doSim(end=10.0, points=20.0)
```

3. Or using `mod.doSimPlot()` which runs the simulation and displays the results. In addition to `doSim`'s arguments the following arguments may be used:

```
mod.doSimPlot(end=10.0, points=21, plot='species', fmt='lines', filename=None)
```

where:

- *plot* can be one of species, rates or all.
- *fmt* plot format, UPI backend dependent (default='') or the *CommonStyle* 'lines' or 'points'.
- *filename* if not None (default) then the plot is exported as *filename.png*

Another way of quickly visualising the results of a simulation is to use the `mod.SimPlot` method:

```
mod.SimPlot(plot='species', filename=None, title=None, log=None, format='lines')
```

where:

- *plot*: output to plot (default='species')
- 'all' rates and species
- 'species' species
- 'rates' reaction rates
- [*SI*, *RI*,] a list of model attributes (species, rates)
- *filename* (optional) if not None file is exported to filename (default=None)
- *title* the plot title (default=None)
- *log* use log axis for 'x', 'y', 'xy' (default=None)
- *fnt* plot format, UPI backend dependent (default='') or the *CommonStyle* 'lines' or 'points'.

Called without arguments, `mod.SimPlot()` plots all the species concentrations against time.

6.1 Simulation results

In PySCeS 0.7.x the simulation results have been consolidated into a new `mod.data_sim` object. By default species concentrations/amounts, reaction rates and rate rules are automatically added to the *data_sim* object. If extra information (parameters, compartments, assignment rules) is required this can easily be added using `mod.CVODE_extra_output`, a list containing any model attribute which is not added by default.

The `mod.data_sim` object which has many methods for extracting simulation data including:

- `data_sim.getTime()` return a vector of time points
- `data_sim.getSpecies()` returns array([[time], [species]])
- `data_sim.getRates()` returns array([[time], [rates]])
- `data_sim.getRules()` returns array([[time], [rate rules]])
- `data_sim.getXData` returns array([[time], [CVODE_extra_output]])
- `data_sim.getSimData(*args)` return an array consisting of *time* plus any available data series:

```
mod.data_sim.getSimdata('s1', 'R1', 'Rule1', 'xData2')
```

- `data_sim.getAllSimData(*args)` return an array of all simulation data
- `data_sim.getDataAtTime(time)` return the results of the simulation at *time*.

- `data_sim.getDataInTimeInterval(time, bound)` return the simulation data in the interval `[time-bound, time+bound]`, if `bound` is not specified it is assumed to be the step size.

All the `data_sim.get*` methods by default only return a NumPy array containing the requested data, however if the argument `lbls` is set to `True` then both the array as well as a list of column labels is returned:

```
Sdata, Slabels = mod.data_sim.getSpecies(lbls=True)
```

This is very useful when using the PySCeS plotting interface (described later in this guide) to plot simulation results.

6.2 Advanced

PySCeS sets integrator options that attempt to configure the integration algorithms to suit a particular model. However, almost every integrator option can be overridden by the user. Simulator settings are stored in PySCeS `mod.__settings__` dictionary. For LSODA some useful keys are (`mod.__settings__[key]`):

```
'lsoda_atol': 1.0e-012
'lsoda_rtol': 1.0e-007
'lsoda_mxordn': 12
'lsoda_mxords': 5
'lsoda_mxstep': 0
```

`atol` and `rtol` are the absolute and relative tolerances, while `mxstep=0` means that LSODA chooses the number of steps (up to 500). If this is still not enough, PySCeS automatically increases the number of steps necessary to find a solution.

Additionally, CVODE allows per step step-size optimisation and automatic tolerance scaling:

```
'cvsode_abstol': 1.0e-15
'cvsode_abstol_factor': 1.0e-8
'cvsode_auto_tol_adjust': True
'cvsode_mxstep': 1000
'cvsode_reltol': 1.0e-9
'cvsode_stats': False
```

`cvsode_abstol` is considered to be the minimum absolute tolerance, PySCeS first uses the initial species values multiplied by `cvsode_abstol_factor` (so that `[s]*[factor] >= [abstol]`) to calculate its absolute tolerance. Once the simulation is underway PySCeS periodically readjusts the absolute tolerance on a per species basis based on the current species value.

If CVODE cannot find a solution in the given number of steps it automatically increases `cvsode_mxstep` and tries again, however, it also keeps track of the number of times that this adjustment is required and if a specific threshold is passed it will begin to increase `cvsode_reltol` by 1.0e3 (to a maximal value of 1.0e-3). Finally, if `cvsode_stats` is enabled CVODE will display a report of its internal parameters after the simulation is complete.

STEADY-STATE ANALYSIS

PySCeS solves for a steady state using either the non-linear solvers **HYBRD**, **NLEQ2** or forward integration. By default PySCeS has *solver fallback* enabled which means that if a solver fails or returns an invalid result (i.e., contains negative concentrations) it switches to the next available solver. The solver chain is as follows:

1. **HYBRD** (can handle ‘rough’ initial conditions, converges quickly).
2. **NLEQ2** (highly optimised for extremely non-linear systems, more sensitive to bad conditioning and slightly slower convergence).
3. **FINTSLV** (finds a result when the change in $\max([\text{species}])$ is less than 0.1%; slow convergence).

Solver fallback can be disabled by setting `mod.mode_solver_fallback = 0`. Each of the three solvers is highly configurable and although the default settings should work for most models configurable options can be set in by way of the `mod.__settings__` dictionary.

To calculate a steady state use the `mod.doState()` method:

```
>>> mod.doState()
(hybrd) The solution converged.
```

The results of a steady-state evaluation are stored as arrays as well as individual attributes and can be easily displayed using the `mod.showState()` method:

- `mod.showState()` displays the current steady-state values of both the species and fluxes.
- For each reaction (e.g. `R2`) a new attribute `mod.J_R2`, which represents its steady-state value, is created.
- Similarly, each species (e.g. `mod.s2`) has a steady-state attribute `mod.s2_ss`
- `mod.state_species` in `mod.species` order.
- `mod.state_flux` in `mod.reactions` order.

There are various ways of initialising the steady-state solvers although, in general, the default values can be used.

- `mod.mode_state_init` initialises the solver using either the initial values (0), a value close to zero (1). The default behaviour is to use the initial values.

7.1 New: `mod.data_sstate`

New to PySCeS 0.7 is the `mod.data_sstate` object that by default stores steady-state data (species, fluxes, rate rules) in a manner similar to `mod.data_sim`. One notable exception is that the current steady-state values are also made available as attributes to this object (e.g. species S1's steady-state value is stored as `mod.data_sstate.S1`). Using the `mod.STATE_extra_output` list it is possible to store user defined data in the `data_sstate` object. Steady-state data can be easily retrieved using the by now familiar `.get*` methods.

- `data_sstate.getSpecies()` returns a species array
- `data_sstate.getFluxes()` returns a flux array
- `data_sstate.getRules()` returns a rate rule array
- `data_sstate.getXData()` returns an array defined in `STATE_extra_output`
- `data_sstate.getStateData(*args)` return user defined array of data ('S1','R2')
- `data_sstate.getAllStateData()` return all state data as an array

All these methods also accept the `lbls=True` argument in which case they return both array data and a label list:

```
ssdat, sslbl = mod.data_sstate.getSpecies(lbls=True)
```

7.2 Stability

PySCeS can analyse the stability of systems that can attain a steady state. It does this by calculating the Eigen values of the Jacobian matrix for the reduced system of independent ODE's:

```
- ``mod.doEigen()`` calculates a steady-state and performs the stability analysis
- ``mod.showEigen`` prints out a stability report
- ``mod.doEigenShow()`` combines both of the above
```

The Eigen values are also available as attributes `mod.lambda1` etc. By default the Eigen values are stored as `mod.eigen_values` but if `mod.__settings__['mode_eigen_output'] = 1` is set both the Eigen values as well as the left and right Eigen vectors are stored as `mod.eigen_vecleft` and `mod.eigen_vecright` respectively. Please note that there is currently no guarantee that the order of the Eigen value array corresponds to the species order.

METABOLIC CONTROL ANALYSIS

For practical purposes the following methods are collected into a set of meta-routines that all first solve for a steady state and then the required Metabolic Control Analysis (MCA) ^{1, 2} evaluation methods.

8.1 Elasticities

The elasticities towards both the variable species and parameters can be calculated using `mod.doElas()` which generates as output:

- Scaled elasticities generated as `mod.ecRate_Species`, e.g. `mod.ecR4_s2`
- `mod.showEvar()` displays the non-zero elasticities calculated with respect to the variable species.
- `mod.showEpar()` displays the non-zero parameter elasticities.

As a prototype we also store the elasticities in an object, `mod.ec.*` this may become the default way of accessing elasticity data in future releases but has not been stabilised yet.

8.2 Control coefficients

Both control coefficients and elasticities can be calculated using a single method, `mod.doMca()`.

- `mod.showCC()` displays the complete set of flux and concentration control coefficients.
- Individual control coefficients are generated as either `mod.ccSpecies_Rate` for a concentration control coefficient, e.g. `mod.ccs1_R4`.
- Similarly, `mod.ccJFlux_Rate` is a flux control coefficient e.g. `mod.ccJR1_R4`.

¹ Kacser, H. and Burns, J. A. (1973), *The control of flux*, Symp. Soc. Exp. Biol. **32**, 65-104.

² Heinrich and Rappoport (1974), *A linear steady-state treatment of enzymatic chains: General properties, control and effector strength*, Eur. J. Biochem. **42**, 89-95.

As it is generally common practice to use scaled elasticities and control coefficients PySCeS calculated these by default. However, it is possible to generate unscaled elasticities and control coefficients by setting the attribute `mod.__settings__['mode_mca_scaled'] = 0` in which case the model attributes are attached as `mod.uec` and `mod.ucc` respectively.

As a prototype we also store the elasticities in an object, `mod.cc.*` this may become the default way of accessing control coefficient data in future releases but has not been stabilised yet.

8.3 Response coefficients

A new PySCeS feature is the ability to calculate the parameter response coefficients for a model with the `mod.doMcaRC()` method. Unlike the elasticities and control coefficients the response coefficients are made available as a single attribute `mod.rc`. This attribute is a data object, containing the response coefficients as attributes and has the following methods:

- `rc.var_par` individual response coefficients can be accessed as attributes made up of `variable_parameter` e.g. `mod.rc.R1_k1`
- `rc.get('var', 'par')` return a response coefficient
- `rc.list()` returns all response coefficients as a dictionary of {key:value} pairs
- `rc.select('attr', search='a')` select all response coefficients that refer to 'attr' e.g. `select('R1')` or `select('k2')`
- `rc.matrix`: the matrix of response coefficients
- `rc.row`: row labels
- `rc.col`: column labels

8.4 Response coefficients with respect to moiety-conserved sums

The `mod.doMcaRC()` method only calculates response coefficients with respect to explicit model parameters. However, in models with moiety-conservation the total concentration of all the species that form part of a particular moiety-conserved cycle is also a parameter of the model. PySCeS infers such moiety-conserved sums from the initial species concentrations specified by the user. In some cases it might be interesting to consider the effects that a change in the total concentration of a moiety will have on the steady-state. This analysis may be done with the method `mod.doMcaRCT()`.

Since moiety-conserved sums are not explicitly named in PySCeS model files, 'T_' is prepended to all the species names listed in `mod.Consmatrix.row`. For instance, if the dependent species in a moiety-conserved cycle is 'A', then 'T_A' designates the moiety-conserved sum.

The object `mod.rc` is augmented with the results of `mod.doMcaRCT()`. Response coefficients may thus be accessed with `mod.rc.get('var', 'T_par')`.

Part IV

Parameter scanning

SINGLE DIMENSION PARAMETER SCANS

PySCeS has the ability to quickly generate and plot single dimension parameter scans. Scanning a parameter typically involves changing a parameter through a range of values and recalculating the steady state at each step. Two methods are provided which simplify this task, `mod.Scan1()` is provided to generate the scan data while `mod.Scan1Plot()` is used to visualise the results. The first step is to define the scan parameters:

- `mod.scan_in` is a string defining the parameter to be scanned e.g. `'x0'`
- `mod.scan_out` is a list of strings representing the attribute names you would like to track in the output eg. `['J_R1', 'J_R2', 's1_ss', 's2_ss']`
- You also need to define the range of points that you would like to scan over. For a linear range SciPy has a useful function `scipy.linspace(start, end, points)` (SciPy can be accessed by typing `import scipy` in your Python shell). If you need to generate a log range use `scipy.logspace(start, end, points)`.

Both `scipy.linspace` and `scipy.logspace` use the number of points (including the start and end points) in the interval as an input. Additionally, the start and end values of `scipy.logspace` must be entered as indices, e.g. to start the range at 0.1 and end it at 100 you would write `scipy.logspace(-1, 2, steps)`. Setting up a PySCeS scan session might look something like:

```
>>> import scipy
>>> mod.scan_in = 'x0'
>>> mod.scan_out = ['J_R1', 'J_R6', 's2_ss', 's7_ss']
>>> scan_range = scipy.linspace(0, 100, 11)
```

Before starting the parameter scan, it is important to check that all the model attributes involved in the scan do actually exist. For example, `mod.J_R1` is created when `mod.doState()` is executed, likewise all the elasticities (`mod.ecR_S`) and control coefficients (`mod.ccJ_R`) are only created when the `mod.doMca()` method is called. If all the attributes exist you can perform a parameter scan using the `mod.Scan1(scan_range)` method which takes your predefined scan range as an argument:

```
>>> mod.Scan1(scan_range)

Scanning ...
11 (hybrd) The solution converged.
(hybrd) The solution converged ...
```

```
done.
```

When the scan has been successfully completed, the results are stored in the array (`mod.scan_res`) that has `mod.scan_in` as its first column followed by columns that represent the data defined in `mod.scan_out` (if invalid steady states are generated during the scan they are replaced by NaN). `Scan1` also reports the scan parameter values which generated the invalid states.} . If one or more of your input or output parameters is not a valid model attribute, it will be ignored. Once the parameter scan data has been generated, the next step is to visualise it using the `mod.Scan1Plot()` method:

```
>>> mod.Scan1Plot(plot=[], title=None, log=None, format='lines', filename=None)
```

- *plot* if empty `mod.scan_out` is used, otherwise any subset of `mod.scan_out` (default=[])
- *filename* the filename of the PNG file (default=None, no export)
- *title* the plot title (default=None)
- *log* if None a linear axis is assumed otherwise one of ['x','xy','xyz'] (default=None)
- *format* the backend dependent line format (default='lines') or the *CommonStyle* 'lines' or 'points'.

Called without any arguments `Scan1Plot` plots all of `mod.sim_out` against `mod.sim_in`.

TWO DIMENSION PARAMETER SCANS

Two dimension parameter scans can also easily be generated using the `mod.Scan2D` method:

```
>>> mod.Scan2D(p1, p2, output, log=False)
```

- *p1* is a list of [model parameter 1, start value, end value, points]
- *p2* is a list of [model parameter 2, start value, end value, points]
- *output* the steady-state variable e.g. 'J_R1' or 'A_ss'
- *log* if True scan using log ranges for both axes

To plot the results of two dimensional scan use the `mod.Scan2DPlot` method. Note that as Matplotlib cannot produce 3D plots the GnuPlot interface must be active (see the section on plotting later on in this guide):

```
>>> mod.Scan2DPlot(title=None, log=None, format='lines', filename=None)
```

- *filename* the filename of the PNG file (default=None, no export)
- *title* the plot title (default=None)
- *log* if None a linear axis is assumed otherwise one of ['x','xy','xyz'] (default=None)
- *format* the backend dependent line format (default='lines') or the *CommonStyle* 'lines' or 'points'.

MULTI-DIMENSION PARAMETER SCANS

This new PySCeS feature allows multi-dimensional parameter scanning. Any combination of parameters is possible and can be added as *master* parameters that change independently or *slave* parameters whose change is coordinated with the previously defined parameter. Unlike `mod.Scan1()` this function is accessed via the `pysces.Scanner` class that is instantiated with a loaded PySCeS model object:

```
>>> sc1 = pysces.Scanner(mod)
>>> sc1.addScanParameter('x3', 1, 10, 11)
>>> sc1.addScanParameter('k2', 0.1, 1000, 5, log=True)
>>> sc1.addScanParameter('k4', 0.1, 1000, 5, log=True, slave=True)
>>> sc1.addUserOutput('J_R1', 's1_ss')
>>> sc1.Run()

... scan: 55 states analysed

>>> sc1_res = sc1.getResultMatrix()
>>> print sc1_res[0]
array([1., 0.1, 0.1, 97.94286647, 49.1380999])

>>> print sc1_res[-1]
array([1.0e+01, 1.0e+03, 1.0e+03, -3.32564878e+00, 3.84227702e-03])
```

In this scan we define two independent (`x3`, `k2`) and one dependent (`k3`) scan parameters and track the changes in the steady state variables `J_R1` and `s1_ss`. Note that `k2` and `k4` use a logarithmic scale. Once run the input parameters cannot be altered, however, the output can be changed and the scan rerun.

- `sc1.addScanParameter(name, start, end, points, log, slave)` where `name` is the input parameter (as a string), `start` and `end` define the range with the required number of points. While `log` and `slave` are boolean arguments indicating the point distribution and whether the axis is independent or not.
- `sc1.addUserOutput(*args)` an arbitrary number of model attributes to be output can be added (this method automatically tries to determine the level of analysis necessary) e.g. `addUserOutput('J_R1', 'ecR1_k2')`
- `sc1.Run()` run the scan, if subsequent runs are required after changing output parameters use `sc1.RunAgain()`. Note that it is not possible to change the input parameters once a scan has been run, if this is required a new `Scanner` object should be created.

- `sc1.getResultMatrix(stst=False)` return the scan results as an array containing both input and output if `stst = True` append the steady-state fluxes and concentrations to the user output so that output has dimensions `[scan_parameters]+[state_species+state_flux]+[Useroutput]` otherwise return the default `[scan_parameters]+[Useroutput]`.
- `sc1.UserOutputList` the list of output names
- `sc1.UserOutputResults` an array containing only the output
- `sc1.ScanSpace` the generated list of input parameters.

Part V

Plotting

The PySCeS plotting interface has been completely rewritten to facilitate the use of multiple plotting back-ends via a Unified Plotting Interface (UPI). Using the UPI we ensure that a specified subset of plotting methods is back-end independent (although the UPI can be extended with back-end specific methods). So far Matplotlib (default) and GnuPlot back-ends have been implemented.

The common UPI functionality is accessible as `pysces.plt.*` while back-end specific functionality is available as `pysces.plt.m` (Matplotlib) and `pysces.plt.g` (GnuPlot).

While the Matplotlib is activated by default GnuPlot needs to be enabled (see Configuring PySCeS section) and then activated using `pysces.plt.p_activateInterface('gnuplot')`. All installed interfaces can be activated or deactivated as required:

```
>>> pysces.plt.p_activateInterface(interface)
>>> pysces.plt.p_deactivateInterface(interface)
```

where *interface* is either `'matplotlib'` or `'gnuplot'`. The PySCeS UPI defines currently has the following methods:

`plot(data, x, y, title='', format='')` plot a single line data[y] vs data[x]

- *data* the data array
- *x* x column index
- *y* y column index
- *title* is the line key
- *format* is the backend format string (default='')

`plotLines(data, x, y=[], titles=[], formats=[''])` plot multiple lines
i.e. data[y1, y2,] vs data[x]

- *data* the data array
- *x* x column index
- *y* is a list of line indexes, if empty all of y not including x is plotted
- *titles* a list of line keys, if empty Line1, Line2, etc is used
- *formats* a list (per line) of format strings, if formats only contains a single item, this format is used for all lines.

`splot(data, x, y, z, title='', format='')` plot a surface i.e. data[z] vs data[y] vs data[x]

- *data* the data array
- *x* x column index
- *y* y column index
- *z* z column index
- *title* the surface key

- *format* a format string (default='')

`plotSurfaces(data, x, y, z=[], titles=[], formats=[''])` plot multiple surfaces i.e. `data[z1, z2,]` vs `data[y]` vs `data[x]`

- *data* the data array
- *x* x column index
- *y* y column index
- *z* a list of z column indexes, if empty all data not including x, y are plotted
- *titles* a list of surface keys, if empty Surf1, Surf2 etc. is used
- *formats* is a list (per line) of format strings (default='')

If *formats* only contains a single item, this format is used for all surfaces.

`replot()` replot the current figure using all active interfaces (useful with GnuPlot type interfaces)

`save(name, directory=None, dfmt='%.8e')` save the plot data and (if possible) the back-end specific format file

- *filename* the filename
- *directory* optional (default = current working directory)
- *dfmt* the data format string (default='%.8e')

`export(name, directory=None, type='png')` export the current plot as a <format> file (currently only PNG is guaranteed to be available on all back-ends).

- *filename* the filename
- *directory* optional (default = current working directory)
- *type* the file format (default='png').

`setGraphTitle(title='PySCeS Plot')` set the graph title, unset if *title=None*

- *title* (string, default='PySCeS Plot') the graph title

`setAxisLabel(axis, label='')` sets one or more axis label

- *axis* x, y, z, xy, xz, yz, zyx
- *label* label string (default=None)

Called with only the axis argument clears that axis' label.

`setKey(value=False)` enable or disable the current plot key, no arguments removes key.

- *value* boolean (default = False)

`setLogScale(axis)` set *axis* to log scale

- *axis* is one of x, y, z, xy, xz, yz, zyx

`setNoLogScale(axis)` set axis to a linear scale

- *axis* is one of x, y, z, xy, xz, yz, zyx

`setRange(axis, min=None, max=None)` set one or more axis range

- *axis* is one of x, y, z, xy, xz, yz, zyx
- *min* is the range(s) lower bound (default=None, back-end auto-scales)
- *max* range(s) upper bound (default=None, back-end auto-scales)

`setGrid(value)` enable or disable the graph grid

- *value* (boolean) True (on) or False (off)

`plt.closeAll()` Close all active Matplotlib figures

Part VI

Displaying data

DISPLAYING/SAVING MODEL ATTRIBUTES

All of the `showX()` methods, with the exception of `mod.showModel()` operate in exactly the same way. If called without an argument, they display the relevant information to the screen. Alternatively, if given an open, writable (ASCII mode) file object as an argument, they write the requested information to the open file. This allows the generation of customised reports containing only information relevant to the model.

- `mod.showSpecies()` prints the current value of the model species (`mod.M`).
- `mod.showSpeciesI()` prints the initial, parsed in, value of the model species (`mod.Mi`).
- `mod.showPar()` prints the current value of the model parameters.
- `mod.showState()` prints the current steady-state fluxes and species.
- `mod.showConserved()` prints any moiety conserved relationships (if present).
- `mod.showFluxRelationships()` shows the relationships between dependent and independent fluxes at steady state
- `mod.showRateEq()` prints the reaction stoichiometry and rate equations.
- `mod.showODE()` prints the differential equations.

Please note that the `mod.showModel()` method is not recommended for saving models as a PySCeS input file instead use the Core2 based `pysces.interface.writeMod2PSC` method instead:

```
>>> pysces.interface.writeMod2PSC(mod, filename, directory, iValues=True, getstrbuf=True)
```

- *filename*: writes `<filename>.psc` or `<model_name>.psc` if None
- *directory*: (optional) an output directory
- *iValues*: if True (default) then the models initial values are used (or the current values if False).
- *getstrbuf*: if True a StringIO buffer is returned instead of writing to disk

Assuming you have loaded a model and run `mod.doState()` the following code opens a Python file object (`rFile`), writes the steady-state results to the file associated with the file object (`results.txt`) and then closes it again:

```
>>> rFile = file('results.txt','w')
>>> mod.showState()      # print the results to screen
>>> mod.showState(rFile) # write the results to the file results.txt
>>> rFile.close()
```

WRITING FORMATTED ARRAYS

The `showX()` methods described in the previous sections allow the user a convenient way to write the predefined matrices either to screen or file. However, for maximum flexibility, PySCeS includes a suite of array writers that enable one to easily write, in a variety of formats any array to a file. Unlike the `showX()` methods, the `Write_array` methods are specifically designed to write to data to a file.

In most modelling situations it is rare that an array needs to be stored or displayed that does not have specific labels for its rows or columns. Therefore, all the `Write_array` methods take list arguments that can contain either the row or column labels. Obviously, these lists should be equal in length to the matrix dimension they describe and in the correct order.

There are currently three custom array writing methods that work either with a 1D (vector) or 2D arrays (matrices). To allow an easy comparison of the output of these methods, all the following sections use the same example array as input.

13.1 `Write_array()`

The basic array writer is the `Write_array()` method. Using the default settings this method writes a ‘tab delimited’ array to a file. It is trivial to change this to a ‘comma delimited’ format by using the `separator = ‘ ’` argument. Numbers in the array are formatted using the global number format.

If column headings are supplied using the `Col = []` argument they are written above the relevant column and if necessary truncated to fit the column width. If a column name is truncated it is marked with a `*` and the full length name is written as a comment after the array data. Similarly row data can be supplied using the `Row = []` argument in which case the row names are displayed as a comment which is written after the array data.

Finally, if the `close_file` argument is enabled the supplied file object is automatically closed after writing the array. The full call to the method is:

```
>>> mod.Write_array(input, File=None, Row=None, Col=None, separator='')
```

which generates the array

```
## Write_array_linear1_11:12:23
#s0          s1          s2
```

```
-3.0043e-001  0.0000e+000  0.0000e+000
 1.5022e+000 -5.0217e-001  0.0000e+000
 0.0000e+000  1.5065e+000 -5.0650e-001
 0.0000e+000  0.0000e+000  1.0130e+000
# Row: R1 R2 R3 R4
```

By default, each time an array is written, PySCeS includes an array header consisting of the model name and the time the array was written. This behaviour can be disabled by setting: `mod.write_array_header = 0`

13.2 Write_array_latex()

The `Write_array_latex()` method functions similarly to the generic `Write_array()` method except that it generates a formatted array that can be included directly in a LaTeX document. Additionally, there is no separator argument, column headings are not truncated and row labels appear to the left of the matrix.

```
>>> mod.Write_array_latex(input, File=None, Row=None, Col=None)
```

which generates

```
%% Write_array_latex_linear1_11:45:03
\[
\begin{array}{r|rrr}
& \small{s0} & \small{s1} & \small{s2} \\ \hline
\small{R1} & -0.3004 & 0.0000 & 0.0000 \\
\small{R2} & 1.5022 & -0.5022 & 0.0000 \\
\small{R3} & 0.0000 & 1.5065 & -0.5065 \\
\small{R4} & 0.0000 & 0.0000 & 1.0130 \\
\end{array}
\]
```

and in a typeset document appears as:

	s0	s1	s2
R1	-0.3004	0.0000	0.0000
R2	1.5022	-0.5022	0.0000
R3	0.0000	1.5065	-0.5065
R4	0.0000	0.0000	1.0130

Part VII

Installing and configuring

Before installing or building PySCeS the following software is required:

- Python 2.5 (or 2.4 plus the Elementtree/cElementtree packages)
- Numpy 1.2+
- SciPy 0.7.0 (0.6.x will work with NumPy > 1.0.5)
- GCC 4.2+ on Linux or MinGW GCC 3.4.5 on Windows is required for building PySCeS from source only
- Matplotlib 0.98.3 with the TkAgg backend (this is the default, but optional, plotting package but can be replaced with GnuPlot)

optional, but highly recommended, packages:

- libSBML 3.x install with the Python bindings for SBML support
- GnuPlot alternative plotting back-end
- iPython highly recommended for interactive modelling sessions
- SciTE editor for editing and running PySCeS based modelling programs

This software stack provides a powerful scientific programming platform which is used by PySCeS to provide a flexible Systems Biology Modelling environment.

PySCeS 0.7.0 itself has been modularised into a main package and a (growing) number of support modules which extends its core functionality. The most important of these is the advanced simulation support added by installing PySundials (<http://pysundials.sf.net>). Linux users should build and install the SUNDIALS library and PySundials (build instructions on the PySundials web site). Windows users can simply download and install the *pysces_pysundials* module.

- *pysces_pysundials* a binary port of SUNDIALS+PySundials for Windows
- *pysces_metatool* adds elementary mode support to PySCeS using MetaTool
- *pysces_mariner* SOAP based web services gateway, including a PySCeS server and remote client
- *pysces_kraken* (coming soon) PySCeS distributed processing module (currently distributed with PySCeS)

PySCeS and its extension modules use either the Python distutils or the Numpy distutils extensions. Assuming you have working versions of NumPy and SciPy on a Linux type operating systems building PySCeS is as easy as:

```
python setup.py install
```

On Windows (with MinGW) depending on your system configuration this becomes:

```
python setup.py config --compiler=mingw32 build --compiler=mingw32 install
```

In this release we have started prototyping Python egg support (currently only for windows) which is implemented via the *setupegg.py* build scripts.

By default PySCeS installs with a version of ZIB's NLEQ2 non-linear solver. This software is distributed under its own non-commercial licence. Please see the README.txt document provided with this PySCeS installation for details.

CONFIGURING

PySCeS has two configuration (*.ini) files that allows one to specify global (per installation) and local (per user options). Currently the multiuser options are only fully realised on Linux based systems. Global options are stored in the *pyscfg.ini* file which is created in your PySCeS installation directory (this is a Windows version with the Linux defaults indicated with in **value**):

```
[Pysces]
install_dir = c:\python25\lib\site-packages\pysces
gnuplot_dir = c:\model\gnuplot\binaries
model_dir = os.path.join(os.getenv('HOMEDRIVE')+os.path.sep, 'Pysces', 'psc')
output_dir = os.path.join(os.getenv('HOMEDRIVE')+os.path.sep, 'Pysces')
*model_dir = os.path.join(os.path.expanduser('~'), 'Pysces', 'psc') *
*output_dir = os.path.join(os.path.expanduser('~'), 'Pysces') *
```

The *[Pysces]* section contains information on the installation directory, the directory where the GnuPlot executable(s) can be found and the default model file and output directories. As we shall see some of these defaults can be overruled by the local configuration options:

```
[ExternalModules]
nleq2 = True

[PyscesModules]
pitcon = True
```

These sections define whether 3rd party algorithms (e.g. NLEQ2) are available for use, while the last section allows the alternate plotting backends to be enabled or disabled:

```
[PyscesConfig]
gnuplot = True
matplotlib = True
```

The user configuration files (*pys_usercfg.ini*) are created when PySCeS is imported/run for the *first time*. On Windows this is in *<HOMEDRIVE>\Pysces* while on Linux this is in *\$HOME\Pysces*. Once created the user configuration files can be edited and will be used for every subsequent PySCeS session:

```
[Pysces]
output_dir = C:\mypysces
```

```
model_dir = C:\mypysces\pscmodels  
gnuplot = False
```

Here I have customised my default model and output directories and disabled GnuPlot (enabled above). If required *gnuplot_dir* can also be set to point to an alternate location on a per user basis. Once you have PySCeS configured to your personal requirements you are ready to begin modelling.

Part VIII

References

Part IX

The PySCeS Model Description Language

PySCeS: the Python Simulator for Cellular Systems is an extendable toolkit for the analysis and investigation of cellular systems. It is available for download from:

<http://pysces.sf.net>

PySCeS uses an ASCII text based *input file* to describe a cellular system in terms of its stoichiometry, kinetics, compartments and parameters. Input files may have any filename with the single restriction that, for cross platform compatibility, they must end with the extension *.psc*. In this document we describe the PySCeS Model Description Language (MDL) which has been updated and extended for the PySCeS 0.7.x release.

PySCeS is distributed under the PySCeS (BSD style) license and is made freely available as Open Source software. See LICENCE.txt for details.

We hope that you will enjoy using our software. If, however, you find any unexpected features (i.e. bugs) or have any suggestions on how we can improve PySCeS and specifically the PySCeS MDL please let us know.

DEFINING A PYSCeS MODEL

15.1 A kinetic model

The basic description of a kinetic model in the PySCeS MDL contains the following information:

- whether any fixed (boundary) species are present
- the reaction network stoichiometry
- rate equations for each reaction step
- parameter and boundary species initial values
- the initial values of the variable species

Although it is in principle possible to define an ODE based model without reactions or free species, for practical purposes PySCeS requires a minimum of a single reaction. Once this information is obtained it can be organised and written as a PySCeS input file. While this list is the minimum information required for a PySCeS input file the MDL allows the definition of advanced models that contain compartments, global units, functions, rate and assignment rules.

15.2 Model keywords

In PySCeS 0.7.x it is now possible to define keywords that specify model information. Keywords have the general form

`<keyword>: <value>`

The *Modelname* (optional) keyword, containing only alphanumeric characters (or `_`), describes the model filename (typically used when the model is exported via the PySCeS interface module) while the *Description* keyword is a (short) single line model description.

```
Modelname: rohwer_sucrose1
Description: Sucrose metabolism in sugar cane (Johann M. Rohwer)
```

Two keywords are available for use (optional) with models that have one or more compartments defined. Both take a boolean (True/False) as their value:

- *Species_In_Conc* specifies whether the species symbols used in the rate equations represent a concentration (True, default) or an amount (False).
- *Output_In_Conc* tells PySCeS to output the results of numerical operations in concentrations (True, default) or in amounts (False).

```
Species_In_Conc: True
Output_In_Conc: False
```

More information on the effect these keywords have on the analysis of a model can be found in the PySCeS Reference Manual.

15.3 Global unit definition

PySCeS 0.7 supports the (optional) definition of a set of global units. In doing so we have chosen to follow the general approach used in the Systems Biology Modelling Language (SBML L2V3) specification. The general definition of a PySCeS unit is: `<UnitType>: <kind>, <multiplier>, <scale>, <exponent>` where *kind* is a string describing the base unit (for SBML compatibility this should be an SI unit) e.g. mole, litre, second or metre. The base unit is modified by the multiplier, scale and index using the following relationship: $\langle multiplier \rangle * (\langle kind \rangle * 10^{*\langle scale \rangle})^{*\langle index \rangle}$. The default unit definitions are:

```
UnitSubstance: mole, 1, 0, 1
UnitVolume: litre, 1, 0, 1
UnitTime: second, 1, 0, 1
UnitLength: metre, 1, 0, 1
UnitArea: metre, 1, 0, 2
```

Please note that defining these values does not affect the numerical analysis of the model in any way.

15.4 Symbol names and comments

Symbol names (i.e. reaction, species, compartment, function, rule and parameter names etc.) must start with either an underscore or letter and be followed by any combination of alphanumeric characters or an underscore. Like all other elements of the input file names are case sensitive:

```
R1
_subA
par1b
ext_1
```

Explicit access to the “current” time in a time simulation is provided by the special symbol `_TIME_`. This is useful in the definition of events and rules (see chapter on advanced model construction for more details).

Comments can be placed anywhere in the input file in one of two ways, as single line comment starting with a # or as a multi-line triple quoted comment “”“<comment>”””:

```
# everything after this is ignored

"""
This is a comment
spread over a
few lines.
"""
```

15.5 Compartment definition

By default (as is the case in all PySCeS versions < 0.7) PySCeS assumes that the model exists in a single unit volume compartment. In this case it is **not** necessary to define a compartment and the ODE’s therefore describe changes in concentration per time. However, if a compartment is defined, PySCeS assumes that the ODE’s describe changes in substance amount per time. Doing this affects how the model is defined in the input file (especially with respect to the definitions of rate equations and species) and the user is **strongly** advised to read the Users Guide before building models in this way. The compartment definition is as follows
Compartment: <name>, <size>, <dimensions>, where <name> is the unique compartment id, <size> is the size of the compartment (i.e. length, volume or area) defined by the number of <dimensions> (e.g. 1,2,3):

```
Compartment: Cell, 2.0, 3
Compartment: Memb, 1.0, 2
```

15.6 Function definitions

A new addition to the PySCeS MDL is the ability to define SBML styled functions. Simply put these are code substitutions that can be used in rate equation definitions to, for example, simplify the kinetic law. The general syntax for a function is Function: <name>, <args> {<formula>} where <name> is the unique function id, <arglist> is one or more comma separated function arguments. The <formula> field, enclosed in curly brackets, may only make use of arguments listed in the <arglist> and therefore **cannot** reference model attributes directly. If this functionality is required a forcing function (assignment rule) may be what you are looking for.

```
Function: rmm_num, Vf, s, p, Keq {
Vf*(s - p/Keq)
}

Function: rmm_den, s, p, Ks, Kp {
s + Ks*(1.0 + p/Kp)
}
```

The syntax for function definitions has been adapted from Frank Bergmann and Herbert Sauro's "Human Readable Model Definition Language" (Draft 1).

15.7 Defining fixed species

Boundary species, also known as fixed or external species, are a special class of parameter used when modelling biological systems. The PySCeS MDL fixed species are declared on a single line as `FIX: <fixedlist>`. The `<fixedlist>` is a space separated list of symbol names which should be initialised like any other species or parameter:

```
FIX: Fru_ex Glc_ex ATP ADP UDP phos glycolysis Suc_vac
```

If no fixed species are present in the model then this declaration should be omitted entirely.

15.8 Reaction stoichiometry and rate equations

The reaction stoichiometry and rate equation are defined together as a single reaction step. Each step in the system is defined as having a name (identifier), a stoichiometry (substrates are converted to products) and rate equation (the catalytic activity, described in terms of species and parameters). All reaction definitions should be separated by an empty line. The general format of a reaction in a model with no compartments is:

```
<name>:
    <stoichiometry>
    <rate equation>
```

The `<name>` argument follows the syntax as discussed in a previous section, however, when more than one compartment has been defined it is important to locate the reaction in its specific compartment. This is done using the `@` operator:

```
<name>@<compartment>:
    <stoichiometry>
    <rate equation>
```

Where `<compartment>` is a valid compartment name. In either case this then followed either directly (or on the next line) by the reaction stoichiometry.

Each `<stoichiometry>` argument is defined in terms of reaction substrates, appearing on the left hand side and products on the right hand side of an identifier which labels the reaction as either reversible (`=`) or irreversible (`>`). If required each reagent's stoichiometric coefficient (PySCeS accepts both integer and floating point) should be included in curly braces `{}` immediately preceding the reagent name. If these are omitted a coefficient of one is assumed:

```
{2.0}Hex_P = Suc6P + UDP # reversible reaction
Fru_ex > Fru # irreversible reaction
species_5 > $pool # a reaction to a sink
```

The PySCeS MDL also allows the use of the `$pool` token that represents a placeholder reagent for reactions that have no net substrate or product. Reversibility of a reaction is only used when

exporting the model to other formats (such as SBML) and in the calculation of elementary modes. It does not affect the numerical evaluation of the rate equations in any way.

Central to any reaction definition is the *<rate equation>* (SBML kinetic law). This should be written as valid Python expression and may fall across more than one line. Standard Python operators `+` `-` `*` `/` `**` are supported (note the Python power e.g. 2^4 is written as `2**4`). There is no shorthand for multiplication with a bracket so $-2(a+b)^h$ would be written as `-2*(a+b)**h` and normal operator precedence applies:

<code>+, -</code>	addition, subtraction
<code>*, /</code>	multiplication, division
<code>+x, -x</code>	positive, negative
<code>**</code>	exponentiation

Operator precedence increase from top to bottom and left to right (adapted from the Python Reference Manual).

The PySCeS MDL parser has been developed to parse and translate different styles of infix into Python/NumPy based expressions, the following functions are supported in any mathematical expression:

- `log`, `log10`, `ln`, `abs`
- `pow`, `exp`, `root`, `sqrt`
- `sin`, `cos`, `tan`, `sinh`, `cosh`, `tanh`
- `arccos`, `arccosh`, `arcsin`, `arcsinh`, `arctan`, `arctanh`
- `floor`, `ceil`, `ceiling`, `piecewise`
- `notanumber`, `pi`, `infinity`, `exponentiale`

Logical operators are supported in rules, events etc but *not* in rate equation definitions. The PySCeS parser understands Python infix as well as libSBML and NumPy prefix notation.

- `and` or `xor` or `not`
- `>` `gt(x,y)` `greater(x,y)`
- `<` `lt(x,y)` `less(x,y)`
- `>=` `ge(x,y)` `geq(x,y)` `greater_equal(x,y)`
- `<=` `le(x,y)` `leq(x,y)` `less_equal(x,y)`
- `==` `eq(x,y)` `equal(x,y)`
- `!=` `neq(x,y)` `not_equal(x,y)`

Note that currently the MathML *delay* and *factorial* functions are not supported. Delay is handled by simply removing it from any expression, e.g. `delay(f(x))` would be parsed as `f(x)`. Support for *piecewise* has been recently added to PySCeS and will be discussed in the *advanced features* section.

A reaction definition when no compartments are defined:

```
R5: Fru + ATP = Hex_P + ADP
      Fru/Ki5_Fru) * (Fru/Km5_Fru) * (ATP/Km5_ATP) / (1 +
      Vmax5 / (1 + Fru/Ki5_Fru) * (Fru/Km5_Fru) * (ATP/Km5_ATP) / (1 +
      Fru/Km5_Fru + ATP/Km5_ATP + Fru*ATP / (Km5_Fru*Km5_ATP) +
      ADP/Ki5_ADP)
```

and using the previously defined functions:

```
R6:
      A = B
      rmm_num(V2, A, B, Keq2) / rmm_den(A, B, K2A, K2B)
```

When compartments are defined note how now the reaction is now given a location and that because the ODE's formed from these reactions must be in changes in substance per time the rate equation is multiplied by its compartment size. In this particular example the species symbols represent concentrations (*Species_In_Conc: True*):

```
R1@Cell:
      s1 = s2
      Cell * (Vf1 * (s1 - s2/Keq1) / (s1 + KS1 * (1 + s2/KP1)))
```

If *Species_In_Conc: True* the location of the species is defined when it is initialised and will be explained later in this manual. The following example shows the species symbols explicitly defined as amounts (*Species_In_Conc: False*):

```
R4@Memb: s3 = s4
      Memb * (Vf4 * ((s3/Memb) - (s4/Cell) / Keq4) / ((s3/Memb)
      + KS4 * (1 + (s4/Cell) / KP4)))
```

Please note that at this time we are not certain if this form of rate equation is translatable into valid SBML in a way that is interoperable with other software.

15.9 Species and parameter initialisation

The general form of any species (fixed, free) and parameter is simply:

```
property = value
```

Initialisations can be written in any order anywhere in the input file but for human readability purposes these are usually placed after the reaction that uses them or grouped at the end of the input file. Both decimal and scientific notation is allowed with the following provisions that neither floating point (*1.*) nor scientific shorthand (*1.e-3*) syntax should be used, instead use the full form (*1.0e-3*), (*0.001*) or (*1.0*).

Variable or free species are initialised differently depending on whether compartments are present in the model. While in essence the variables are set by the system parameters the

Although the variable species concentrations are determined by the parameters of the system, their initial values are used in various places, calculating total moiety concentrations (if present), time simulation initial values (e.g. time=zero) and as initial guesses for the steady-state algorithms. If an empty initial species pool is required it is not recommended to initialise

these values to zero (in order to prevent potential divide-by-zero errors) but rather to a small value (e.g. 10^{-8}).

For a model with no compartments these initial values assumed to be concentrations:

```
NADH = 0.001
ATP   = 2.3e-3
sucrose = 1
```

In a model with compartments it is expected that the species are located in a compartment (even if *Species_In_Conc: False*) this is done using the @ symbol:

```
s1@Memb = 0.01
s2@Cell = 2.0e-4
```

A word of warning, the user is responsible for making sure that the units of the initialised species match those of the model. Please keep in mind that **all** species (and anything that depends on them) is defined in terms of the *Species_In_Conc* keyword. For example, if the preceding initialisations were for *R1* (see Reaction section) then they would be concentrations (as *Species_In_Conc: True*). However, in the next example, we are initialising species for *R4* and they are therefore in amounts (*Species_In_Conc: False*):

```
s3@Memb = 1.0
s4@Cell = 2.0
```

Fixed species are defined in a similar way and although technically a parameter, they should be given a location in compartmental models:

```
# InitExt
X0 = 10.0
X4@Cell = 1.0
```

However, fixed species are true parameters in the sense that their associated compartment size does not affect their value when it changes size. If compartment size dependent behaviour is required an assignment or rate rule should be considered.

Finally, the parameters should be initialised. PySCeS checks if a parameter is defined that is not present in the rate equations and if such parameter initialisations are detected a harmless warning is generated. If, on the other hand, an uninitialised parameter is detected a warning is generated and a value of 1.0 assigned:

```
# InitPar
Vf2 = 10.0
Ks4 = 1.0
```


ADVANCED MODEL CONSTRUCTION

16.1 Assignment rules

Assignment rules or forcing functions are used to set the value of a model attribute before the ODE's are evaluated. This model attribute can either be a parameter used in the rate equations (this is traditionally used to describe an equilibrium block) a compartment or an arbitrary parameter (commonly used to define some sort of tracking function). Assignment rules can access other model attributes directly and have the generic form `!F <par> = <formula>`. Where `<par>` is the parameter assigned the result of `<formula>`. Assignment rules can be defined anywhere in the input file:

```
!F S_V_Ratio = Mem_Area/Vcyt
!F sigma_test = sigma_P*Pmem + sigma_L*Lmem
```

These rules would set the value of `<par>` which whose value can be followed with using the simulation and steady state `extra_data` functionality.

16.2 Rate rules

PySCeS now includes support for rate rules which are essentially directly encoded ODE's which are evaluated after the ODE's defined by the model stoichiometry and rate equations. Unlike the SBML rate rule, PySCeS allows one to access a reaction symbol in the rate rules (this is automatically expanded when the model is exported to SBML). The general form of a rate rule is `RateRule: <par> {<function>}`. Where `<name>` is the model attribute (e.g. compartment or parameter) whose rate of change is described by the `<formula>`. It may also be defined anywhere in the input file:

```
RateRule: Mem_Area {
  (sigma_P) * (Mem_Area*k4*(P)) + (sigma_L) * (Mem_Area*k5*(L))
}

RateRule: Vcyt { (1.0/Co) * (R1()) + (1-m1) * R2() + (1-m2) * R3() - R4() - R5() }
```

Remember to initialise any new parameters used in the rate rules.

16.3 Events

Time dependant events may now be defined whose definition follows the event framework described in the SBML L2V1 specification. The general form of an event is *Event*: `<name>`, `<trigger>`, `<delay>` { `<assignments>` }. As can be seen an event consists of essentially three parts, a conditional `<trigger>`, a set of one or more `<assignments>` and a `<delay>` between when the trigger is fired (and the assignments are evaluated) and the eventual assignment to the model. Assignments have the general form `<par> = <formula>`. Events have access to the “current” simulation time using the `_TIME_` symbol:

```
Event: event1, _TIME_ > 10 and A > 150.0, 0 {  
V1 = V1*vfact  
V2 = V2*vfact  
}
```

The following event illustrates the use of a delay of ten time units as well as the prefix notation (used by libSBML) for the trigger (PySCeS understands both notations):

```
Event: event2, geq(_TIME_, 15.0), 10 {  
V3 = V3*vfact2  
}
```

Note: in order for PySCeS to handle events it is necessary to have the PySundials installed

16.4 Piecewise

Although technically an operator piecewise functions are sufficiently complicated to warrant their own section. A piecewise operator is essentially an *if, elif, ..., else* logical operator that can be used to conditionally “set” the value of some model attribute. Currently piecewise is supported in rule constructs and has not been tested directly in rate equation definitions. The piecewise function’s most basic incarnation is *piecewise*(`<val1>`, `<cond>`, `<val2>`) which is evaluated as:

```
if <cond>:  
    return <val1>  
else:  
    return <val2>
```

alternatively, *piecewise*(`<val1>`, `<cond1>`, `<val2>`, `<cond2>`, `<val3>`, `<cond3>`):

```
if <cond1>:  
    return <val1>  
elif <cond2>:  
    return <val1>  
elif <cond3>:  
    return <val3>
```

or *piecewise*(`<val1>`, `<cond1>`, `<val2>`, `<cond2>`, `<val3>`, `<cond3>`, `<val4>`):

```

if <cond1>:
    return <val1>
elif <cond2>:
    return <val2>
elif <cond3>:
    return <val3>
else:
    return <val4>

```

can also be used. A “real-life” example of an assignment rule with a piecewise function:

```
!F Ca2plus=piecewise(0.1, lt(_TIME_, 60), 0.1, gt(_TIME_, 66.0115), 1)
```

In principle there is no limit on the amount of conditional statements present in a piecewise function, the condition can be a compound statements *a or b and c* and may include the `_TIME_` symbol.

16.5 Reagent placeholder

Some models contain reactions which are defined as only have substrates or products:

```
R1: A + B >
```

```
R2: > C + D
```

The implication is that the relevant reagents appear or disappear from or into a constant pool. Unfortunately the *PySCeS* parser does not accept such an unbalanced reaction definition and requires these pools to be represented as a `$pool` token:

```
R1: A + B > $pool
```

```
R2: $pool > C + D
```

`$pool` is neither counted as a reagent nor does it ever appear in the stoichiometry (think of it as `dev/null`) and no other `$<str>` tokens are allowed.

EXAMPLE PYSCES INPUT FILES

17.1 Basic model definition

PySCeS test model *pysces_test_linear1.psc*:

```
FIX: x0 x3

R1: x0 = s0
    k1*x0 - k2*s0

R2: s0 = s1
    k3*s0 - k4*s1

R3: s1 = s2
    k5*s1 - k6*s2

R4: s2 = x3
    k7*s2 - k8*x3

# InitExt
x0 = 10.0
x3 = 1.0
# InitPar
k1 = 10.0
k2 = 1.0
k3 = 5.0
k4 = 1.0
k5 = 3.0
k6 = 1.0
k7 = 2.0
k8 = 1.0
# InitVar
s0 = 1.0
s1 = 1.0
s2 = 1.0
```

17.2 Advanced example

This model includes the use of *Compartments*, *KeyWords*, *Units* and *Rules*:

```

Modelname: MWC_wholecell2c
Description: Surovtsev whole cell model using J-HS Hofmeyr's framework

Species_In_Conc: True
Output_In_Conc: True

# Global unit definition
UnitVolume: litre, 1.0, -3, 1
UnitSubstance: mole, 1.0, -6, 1
UnitTime: second, 60, 0, 1

# Compartment definition
Compartment: Vcyt, 1.0, 3
Compartment: Vout, 1.0, 3
Compartment: Mem_Area, 5.15898, 2

FIX: N

R1@Mem_Area: N = M
    Mem_Area*k1*(Pmem)*(N/Vout)

R2@Vcyt: {244}M = P # m1
    Vcyt*k2*(M)

R3@Vcyt: {42}M = L # m2
    Vcyt*k3*(M)*(P)**2

R4@Mem_Area: P = Pmem
    Mem_Area*k4*(P)

R5@Mem_Area: L = Lmem
    Mem_Area*k5*(L)

# Rate rule definition
RateRule: Vcyt {(1.0/Co)*(R1()+ (1-m1)*R2()+ (1-m2)*R3()-R4()-R5())}
RateRule: Mem_Area {(sigma_P)*R4()+ (sigma_L)*R5()}

# Rate rule initialisation
Co = 3.07e5 # uM p_env/(R*T)
m1 = 244
m2 = 42
sigma_P = 0.00069714285714285711
sigma_L = 0.00012

# Assignment rule definition
!F S_V_Ratio = Mem_Area/Vcyt
!F Mconc = (M)/M_init

```



```
!F Lconc = (L)/L_init
!F Pconc = (P)/P_init

# Assignment rule initialisations
M_init = 199693.0
L_init = 102004
P_init = 5303
Mconc = 1.0
Lconc = 1.0
Pconc = 1.0

# Species initialisations
N@Vout = 3.07e5
Pmem@Mem_Area = 37.38415
Lmem@Mem_Area = 8291.2350678770199
M@Vcyt = 199693.0
L@Vcyt = 102004
P@Vcyt = 5303

# Parameter initialisations
k1 = 0.00089709
k2 = 0.000182027
k3 = 1.7539e-010
k4 = 5.0072346e-005
k5 = 0.000574507164

"""
Simulate this model to 200 for maximum happiness and
watch the surface to volume ratio and scaled concentrations.
"""
```

This example illustrates almost all the new features included in the PySCeS MDL. Although it may be slightly more complicated than the basic model described above it is still, by our definition, human readable.

Part X

PySCeS Module documentation

PYSCESUTILS

The PyscesUtils module holds a collection of methods of general use such as timers and array export functionality that can be accessed as **pysces.write**.

`pysces.PyscesUtils.ConvertFileD2U (Filelist)`

Converts a [Filename] from rn to n inplace no effect if the line termination is correct

- Filelist* a file or list of files to convert

`pysces.PyscesUtils.ConvertFileU2D (Filelist)`

Converts a [Filename] from n to rn inplace no effect if the line termination is correct:

- Filelist* a file or list of files to convert

`pysces.PyscesUtils.CopyModels (*args, **kwargs)`

`pysces.PyscesUtils.CopyTestModels (*args, **kwargs)`

class `pysces.PyscesUtils.TimerBox`

A timer “container” class that can be used to hold user defined timers

normal_timer (*name*)

Creates a normal timer method with <name> in the TimerBox instance. Normal timers print the elapsed time since creation when called.

- name* the timer name

reset_step (*name*)

Reset the number of steps of timer <name> in the TimerBox to zero

- name* the step timer whose steps should be reset

step_timer (*name, maxsteps*)

Creates a step timer method with <name> in the TimerBox instance. Step timers print the elapsed time as well as the next step out of maxsteps when called.

- name* the timer name
- maxsteps* the maximum number of steps associated with this timer

stop (*name*)

Delete the timer <name> from the TimerBox instance

- name* the timer name to delete

`pysces.PyscesUtils.VersionCheck (ver='0.1.5')`

class `pysces.PyscesUtils.WriteOutput`

This code is adapted from:

CBMPy: CBTools module

Constraint Based Modelling in Python (<http://cbmpy.sourceforge.net>) Copyright (C) 2009-2016 Brett G. Olivier, VU University Amsterdam, Amsterdam, The Netherlands

exportArray2CSV (*arr*, *fname*)

Export an array to *fname*.csv

- *arr* the an array like object
- *fname* the output filename
- *sep* [default=','] the column separator

exportArray2TXT (*arr*, *fname*)

Export an array to *fname*.txt

- *arr* the an array like object
- *fname* the output filename
- *sep* [default=','] the column separator

exportLabelledArray (*arr*, *names*, *fname*, *sep*=' ', *format*='%f')

Write a 2D array type object to file

- *arr* the an array like object
- *names* the list of row names
- *fname* the output filename
- *sep* [default=','] the column separator
- *format* [default='%s'] the output number format

exportLabelledArray2CSV (*arr*, *names*, *fname*)

Export an array with row names to *fname*.csv

- *arr* the an array like object
- *names* the list of row names
- *fname* the output filename

exportLabelledArray2TXT (*arr*, *names*, *fname*)

Export an array with row names to *fname*.txt

- *arr* the an array like object
- *names* the list of row names
- *fname* the output filename

exportLabelledArrayWithHeader (*arr*, *names*, *header*, *fname*, *sep*=' ', '
format='%f')

Export an array with row names and header

- *arr* the an array like object
- *names* the list of row names
- *header* the list of column names
- *fname* the output filename
- *sep* [default=' '] the column separator
- *format* [default='%s'] the output number format
- *appendlist* [default=False] if True append the array to *fname* otherwise create a new file

exportLabelledArrayWithHeader2CSV (*arr*, *names*, *header*, *fname*)

Export an array with row names and header to *fname.csv*

- *arr* the an array like object
- *names* the list of row names
- *header* the list of column names
- *fname* the output filename

exportLabelledArrayWithHeader2TXT (*arr*, *names*, *header*, *fname*)

Export an array with row names and header to *fname.txt*

- *arr* the an array like object
- *names* the list of row names
- *header* the list of column names
- *fname* the output filename

exportLabelledLinkedList (*arr*, *fname*, *names*=None, *sep*=' ', '
format='%s', *appendlist*=False)

Write a 2D linked list [[...],[...],[...],[...]] and optionally a list of row labels to file:

- *arr* the linked list
- *fname* the output filename
- *names* the list of row names
- *sep* [default=' '] the column separator
- *format* [default='%s'] the output number format
- *appendlist* [default=False] if True append the array to *fname* otherwise create a new file

`pysces.PyscesUtils.str2bool` (*s*)

Tries to convert a string to a Python boolean

- s True if 'True', 'true' or '1' else False

PYSCESPLOT2

PyscesPlot2 is a new graphics subsystem for PySCeS which will include a Unified Plotting Interface which can take advantage of different plotting backends via a common user interface.

class `pysces.PyscesPlot2.FIFOBuffer` (*size*)

Simple fixed size FIFO buffer.

add (*x*)

get ()

class `pysces.PyscesPlot2.GnuPlotUPI` (*work_dir=None, gnuplot_dir=None*)

PySCeS/GnuPlot is reborn, leaner and meaner than ever before. This class enables plotting with GnuPlot via a subprocess link:

- *work_dir* optional argument setting directory for dat file(s)
- *gnuplot_dir* optional argument specifying the location of pgnuplot.exe (win32) or gnuplot

GnuPlot backend to the Unified Plotting Interface.

CommonStyleDefs = {'points': 'w p', 'lines': 'w l'}

DATE_FORMAT = '%.8e'

PAUSE_TIME = 0.1

Terminals = {'windows': '', 'x11': '', 'png': 'medium size 800,600'}

export (*name, directory=None, type='png'*)

Export the current plot as a <format> file.

- *filename* the filename
- *directory* optional (default = current working directory)
- *type* the file format (default='png').

Currently only PNG is guaranteed to be available in all interfaces.

g_file_write_array (*arr, dfmt=None*)

Write a normal (2D) dataset to temp file. Dumps the array to file using the format:

- *arr* the array (*r*>0, *c*>1)

- *fmt* default ‘%.8e’

g_file_write_array3D (*arr*, *yaxis=1*, *dfmt=None*)

Write a GnuPlot format 3D dataset. The *yaxis* argument specifies the column that should be used to split the dataset into GnuPlot slices.

- *arr* the array ($r > 1$, $c > 2$)
- *fmt* default ‘%.8e’
- *yaxis* default 1

g_pause ()

A small pause defined by *self.PAUSE_TIME* (multiplied by 2 when in multiplot).

g_write (*cmd*)

Write a command to the GnuPlot interpreter

- *cmd* the GnuPlot command

plot (*data*, *x*, *y*, *title=''*, *format='w l'*)

Plot a single line data[*y*] vs data[*x*] where:

- *data* the data array
- *x* x column index
- *y* y column index
- *title* is the line key
- *format* is the GnuPlot format string (default='w l')

Format can also be the *CommonStyle* ‘lines’ or ‘points’.

plotLines (*data*, *x*, *y=[]*, *titles=[]*, *formats=['w l']*)

Plot a multiple lines data[*y*₁, *y*₂,] vs data[*x*] where:

- *data* the data array
- *x* x column index
- *y* is a list of line indexes, if empty all of *y* not including *x* is plotted
- *titles* is a list of line keys if empty Line1, Line2, Line3 is used
- *formats* is a list (per line) of GnuPlot format strings (default='w l').

If *formats* only contains a single item, this format is used for all lines and can also be the *CommonStyle* ‘lines’ or ‘points’.

replot ()

Replot the current GnuPlot plot

replotAndWait (*seconds=0.5*)

Replot the current GnuPlot plot and wait default (*seconds* = 0.5) or until enter is pressed (*seconds* = -1)

save (*name*, *directory=None*, *dfmt=None*)

Save the last plot as a GnuPlot file *name.plt* which references *name.dat*.

- name* the name of the GnuPlot plt and and datafile
- directory* (optional) the directory to use (defaults to working directory)
- dfmt* is ignored and uses the value of self.DATF_FORMAT

set (*key*, *value*='')

Send *set* <*key*> or optionally *set* <*key*> <*value*> to GnuPlot.

setAxisLabel (*axis*, *label*='')

Set the axis label:

- axis* = x, y, z, xy, xz, yz, zyx
- label* = string (default='')

Called with only the axis argument clears the axis label.

setDataFileNumberFormat (*format*='%0.8e')

Sets the format string for data written to file

- format* format string (default='%0.8e')

setGraphTitle (*title*='PySCeS Plot')

Set the graph title, unset if title argument is None

- title* (string, default='PySCeS Plot') the graph title

setGrid (*value*)

Display or remove graph grid.

- value* (boolean) True (on) or False (off)

setKey (*value*=False)

Enable or disable the current plot key, no arguments removes key.

- value* boolean (default = False)

setLogScale (*axis*)

Set axis to logscale where:

- axis* = x, y, z, xy, xz, yz, zyx

setMultiplot ()

Begin a multiplot session

setNoLogScale (*axis*)

Set axis to a linear scale where:

- axis* = x, y, z, xy, xz, yz, zyx

setOrigin (*xpos*=0, *ypos*=0)

Set the origin (lower left corner) of the next plot. Uses GnuPlot screen coordinates. If no arguments are supplied reset origin to 0,0.

- xpos* of next plot (default = 0)
- ypos* of next plot (default = 0)

setRange (*axis*, *min=None*, *max=None*)

Set axis range where:

- *axis* = x, y, z, xy, xz, yz, zyx
- *min* = range(s) lower bound (default=None) autoscale
- *max* = range(s) upper bound (default=None) autoscale

If only the *axis* argument is provided, GnuPlot will autoscale the ranges to the data.

setSize (*width=1.0*, *height=1.0*)

Set the size of the next plot relative to the GnuPlot canvas (e.g. screen) size which is defined to be 1. For example if *width* = *height* = 0.5 the plot is 1/4 the size of the viewable canvas. If no arguments are supplied reset size to 1,1.

- *width* of next plot (default = 1.0)
- *height* of next plot (default = 1.0)

setSizeAndOrigin (*width=1*, *height=1*, *xpos=0*, *ypos=0*)

Set the size and origin of the next plot. If no arguments are supplied, reset the size to 1,1 and origin to 0.0

- *width* of next plot (default = 1.0)
- *height* of next plot (default = 1.0)
- *xpos* of next plot (default = 0)
- *ypos* of next plot (default = 0)

setTerminal (*name*, *options=''*)

Sets the terminal, gnuplot: set terminal *name options*

splot (*data*, *x*, *y*, *z*, *titles=''*, *format='w l'*)

Plot a surface data[z] vs data[y] vs data[x] where:

- *data* the data array
- *x* x column index
- *y* y column index
- *z* z column index
- *titles* is the surface key
- *format* is the GnuPlot format string (default='w l')

Format can also be the *CommonStyle* 'lines' or 'points'.

splotSurfaces (*data*, *x*, *y*, *z=[,]*, *titles=[,]*, *formats=['w l']*)

Plot data[z1, z2,] vs data[y] vs data[x] where:

- *data* the data array
- *x* x column index
- *y* y column index

- *z* list of z column indexes, if empty all of z not including x, y are plotted
- *titles* is a list of surface keys, if empty Surf1, Surf2, Surf3 is used
- *formats* is a list (per line) of GnuPlot format strings (default='w l').

If *formats* only contains a single item, this format is used for all surface and can also be the *CommonStyle* 'lines' or 'points'.

unset (*key*, *value*='')

Send *unset* <*key*> or optionally *unset* <*key*> <*value*> to GnuPlot.

unsetMultiplot ()

End a multiplot session.

class `pysces.PyscesPlot2.MatplotlibUPI` (*work_dir*=None, *back-*
end='TkAgg')

Refactored Matplotlib backend to the Unified Plotting Interface

- *work_dir* (optional) working directory

CommonStyleDefs = {'points': 'o', 'lines': '-'}

MAX_OPEN_WINDOWS = 10

closeAll ()

Close all open matplotlib figures.

export (*name*, *directory*=None, *type*='png')

Export the current plot as a <format> file.

- *filename* the filename
- *directory* optional (default = current working directory)
- *type* the file format (default='png').

Currently only PNG is guaranteed to be available in all interfaces.

hold (*hold*=False)

Enable plot holding where each new graph is plotted on top of the previous one.

- *hold* boolean (default = False)

plot (*data*, *x*, *y*, *title*='', *format*='-')

Plot a single line data[*y*] vs data[*x*] where:

- *data* the data array
- *x* x column index
- *y* y column index
- *title* is the line key
- *format* is the Matplotlib format string (default='-')

Format can also be the *CommonStyle* 'lines' or 'points'.

plotLines (*data*, *x*, *y*=[], *titles*=[], *formats*=['-'])

Plot a multiple lines data[*y*1, *y*2,] vs data[*x*] where:

- *data* the data array
- *x* x column index
- *y* is a list of line indexes
- *titles* is a list of line keys
- *formats* is a list (per line) of Matplotlib format strings.

If *formats* only contains a single item, this format is used for all lines and can also be the *CommonStyle* 'lines' or 'points'.

pyplot = None

save (*name*, *directory=None*, *dfmt='%0.8e'*)

Save the plot data to

- *filename* the filename
- *directory* optional (default = current working directory)
- *dfmt* the data format string (default='%.8e')

setAxisLabel (*axis*, *label=''*)

Set the axis label:

- *axis* = x, y, z, xy, xz, yz, zyx
- *label* = string (default='')

Called with only the axis argument clears the axis label.

setGraphTitle (*title='PySCeS Plot'*)

Set the graph title, unset if title=None

- *title* (string, default='PySCeS Plot') the graph title

setGrid (*value*)

Display or remove graph grid.

- *value* (boolean) True (on) or False (off)

setKey (*value=False*)

Enable or disable the current plot key, no arguments removes key.

- *value* boolean (default = False)

setLineWidth (*width=1*)

Sets the line width for current axis

- *width* the line width

setLogScale (*axis*)

Set axis to logscale where:

- *axis* = x, y, z, xy, xz, yz, zyx

setNoLogScale (*axis*)

Set axis to a linear scale where:

- axis* = x, y, z, xy, xz, yz, zyx

setRange (*axis*, *min*=None, *max*=None)

Set axis range where

- axis* = x, y, z, xy, xz, yz, zyx
- min* = range(s) lower bound (default=None) autoscale
- max* = range(s) upper bound (default=None) autoscale

class `pysces.PyscesPlot2.PlotBase`

Abstract class defining the Unified Plotting Interface methods. These methods should be overridden and the class extended by interface specific subclasses.

CommonStyleDefs = {'points': ',', 'lines': '-'}

axisInputStringToList (*input*)

Extracts axis information from a string input, returns a boolean triple representing (x=True/False, y=True/False, z=True/False).

- input* the input string

export (*name*, *directory*=None, *type*='png')

Export the current plot as a <format> file.

- filename* the filename
- directory* optional (default = current working directory)
- type* the file format (default='png').

Currently only PNG is guaranteed to be available in all interfaces.

plot (*data*, *x*, *y*, *title*='', *format*='')

Plot a single line data[y] vs data[x] where:

- data* the data array
- x* x column index
- y* y column index
- title* is the line key
- format* is the XXX format string (default='')

Format can also be the *CommonStyle* 'lines' or 'points'

plotLines (*data*, *x*, *y*=[], *titles*=[], *formats*=[''])

Plot a multiple lines data[y1, y2,] vs data[x] where:

- data* the data array
- x* x column index
- y* is a list of line indexes, if empty all of y not including x is plotted
- titles* is a list of line keys, if empty Line1,Line2,Line3 is used
- formats* is a list (per line) of XXX format strings.

If *formats* only contains a single item, this format is used for all lines and can also be the *CommonStyle* 'lines' or 'points'.

save (*name*, *directory=None*, *dfmt='%0.8e'*)

Save the plot data and (optionally) XXX format file

- *filename* the filename
- *directory* optional (default = current working directory)
- *dfmt* the data format string (default='%.8e')

setAxisLabel (*axis*, *label=''*)

Set the axis label:

- *axis* = x, y, z, xy, xz, yz, zyx
- *label* = string (default='')

Called with only the axis argument clears the axis label.

setGraphTitle (*title='PySCeS Plot'*)

Set the graph title, unset if title=None

- *title* (string, default='PySCeS Plot') the graph title

setGrid (*value*)

Display or remove graph grid.

- *value* (boolean) True (on) or False (off)

setKey (*value=False*)

Enable or disable the current plot key, no arguments removes key.

- *value* boolean (default = False)

setLogScale (*axis*)

Set axis to logscale where:

- *axis* = x, y, z, xy, xz, yz, zyx

setNoLogScale (*axis*)

Set axis to a linear scale where:

- *axis* = x, y, z, xy, xz, yz, zyx

setRange (*axis*, *min=None*, *max=None*)

Set axis range where

- *axis* = x, y, z, xy, xz, yz, zyx
- *min* = range(s) lower bound (default=None) autoscale
- *max* = range(s) upper bound (default=None) autoscale

plot (*data*, *x*, *y*, *z*, *titles=''*, *format=''*)

Plot a surface data[z] vs data[y] vs data[x] where:

- *data* the data array

- *x* x column index
- *y* y column index
- *z* z column index
- *title* is the surface key
- *format* is the XXX format string (default='')

Format can also be the *CommonStyle* 'lines' or 'points'.

plotSurfaces (*data*, *x*, *y*, *z*=[], *titles*=[], *formats*=[''])

Plot data[z1, z2,] vs data[y] vs data[x] where:

- *data* the data array
- *x* x column index
- *y* y column index
- *z* list of z column indexes, if empty all of z not including x, y are plotted
- *titles* is a list of surface keys, if empty Surf1, Surf2, Surf3 is used
- *formats* is a list (per line) of XXX format strings (default='').

If *formats* only contains a single item, this format is used for all surfaces and can also be the *CommonStyle* 'lines' or 'points'.

wait (*seconds*=3)

Wait *seconds* (default = 3) or until enter is pressed (seconds = -1)

class `pysces.PyscesPlot2.PyscesUPI`

This is the frontend to the PySCeS Unified Plotting Interface (`pysces.plt.*`) that allows one to specify which backend should be used to plot when a UPI method is called. More than one interface can be active at the same time and so far the Matplotlib and GnuPlot backends are available for use.

This is an experiment which must be refactored into a more general way of doing things. Basically, I want an instance of the abstract plotting class which will plot to one, any or all currently available backends. If anybody has an idea how I can generate this class automatically please let me know ;-)

closeAll ()

Close all active Matplotlib figures

export (*name*, *directory*=None, *type*='png')

Export the current plot as a <format> file.

- *filename* the filename
- *directory* optional (default = current working directory)
- *type* the file format (default='png').

Currently only PNG is guaranteed to be available in all interfaces.

g = None

m = None

p_activateInterface (*interface*)

Activate an interface that has been set with **p_setInterface()** but deactivated with **p_deactivateInterface**

- *interface* one of ['matplotlib', 'gnuplot']

p_deactivateInterface (*interface*)

Deactivate the interface. This does not delete the interface and it is possible to reactivate the deactivated interface with **p_activateInterface**.

- *interface* one of ['matplotlib', 'gnuplot']

p_setInterface (*name, instance*)

Add an interface to the backend selector

- *name* the interface name currently one of ['matplotlib', 'gnuplot']
- *instance* an instance of a PlotBase derived (UPI) interface

plot (*data, x, y, title='', format=''*)

Plot a single line data[y] vs data[x] where:

- *data* the data array
- *x* x column index
- *y* y column index
- *title* is the line key
- *format* is the backend format string (default='')

plotLines (*data, x, y=[], titles=[], formats=['']*)

Plot a multiple lines data[y1, y2,] vs data[x] where:

- *data* the data array
- *x* x column index
- *y* is a list of line indexes, if empty all of y not including x is plotted
- *titles* is a list of line keys, if empty Line1,Line2,Line3 is used
- *formats* is a list (per line) of XXX format strings.

If *formats* only contains a single item, this format is used for all lines.

replot ()

Replot the current figure for all active interfaces

save (*name, directory=None, dfmt='%0.8e'*)

Save the plot data and (optionally) XXX format file

- *filename* the filename
- *directory* optional (default = current working directory)
- *dfmt* the data format string (default='%0.8e')

setAxisLabel (*axis*, *label*='')

Set the axis label:

- *axis* = x, y, z, xy, xz, yz, zyx
- *label* = string (default=None)

Called with only the axis argument clears the axis label.

setGraphTitle (*title*='PySCeS Plot')

Set the graph title, unset if title=None

- *title* (string, default='PySCeS Plot') the graph title

setGrid (*value*)

Display or remove graph grid.

- *value* (boolean) True (on) or False (off)

setKey (*value*=False)

Enable or disable the current plot key, no arguments removes key.

- *value* boolean (default = False)

setLogScale (*axis*)

Set axis to logscale where:

- *axis* = x, y, z, xy, xz, yz, zyx

setNoLogScale (*axis*)

Set axis to a linear scale where:

- *axis* = x, y, z, xy, xz, yz, zyx

setRange (*axis*, *min*=None, *max*=None)

Set axis range where

- *axis* = x, y, z, xy, xz, yz, zyx
- *min* = range(s) lower bound (default=None) autoscale
- *max* = range(s) upper bound (default=None) autoscale

splot (*data*, *x*, *y*, *z*, *titles*='', *format*='')

Plot a surface data[z] vs data[y] vs data[x] where:

- *data* the data array
- *x* x column index
- *y* y column index
- *z* z column index
- *titles* is a list of surface keys whose len matches data columns
- *format* is the XXX format string (default='')

splotSurfaces (*data*, *x*, *y*, *z*=[], *titles*=[], *formats*=[''])

Plot data[z1, z2,] vs data[y] vs data[x] where:

- *data* the data array
- *x* x column index
- *y* y column index
- *z* list of z column indexes, if empty all of z not including x, y are plotted
- *titles* is a list of surface keys, if empty Surf1, Surf2, Surf3 is used
- *formats* is a list (per line) of XXX format strings (default='').

If *formats* only contains a single item, this format is used for all surfaces.

PYSCESMODEL

This module contains the core PySCeS classes which create the model and associated data objects

class `pysces.PyscesModel.BagOfStuff` (*matrix, row, col*)

A collection of attributes defined by row and column lists used by Response coefficients etc matrix is an array of values while row/col are lists of row column name strings

col = None

get (*attr1, attr2*)

Returns a single attribute “attr1_attr2” or None

list ()

Return all attributes as a attr:val dictionary

listAllOrdered (*order='descending', absolute=True*)

Return an ordered list of (attr, value) tuples

- *order* [default='descending'] the order to return as: 'descending' or 'ascending'

- *absolute* [default=True] use the absolute value

load ()

matrix = None

row = None

select (*attr, search='a'*)

Return a dictionary of <attr>_<name>, <name>_<attr> : val or {} if none If attr exists as an index for both left and right attr then: search='a' : both left and right attributes (default) search='l' : left attributes only search='r' : right attributes

class `pysces.PyscesModel.Event` (*name, mod*)

Event's have triggers and fire EventAssignments when required. Ported from Core2.

assignments = None

code_string = None

delay = 0.0

formula = None

```
mod = None
piecewises = None
reset ()
setAssignment (var, formula)
setTrigger (formula, delay=0.0)
state = False
state0 = False
symbols = None
trigger = None
xcode = None
```

class `pysces.PyscesModel.EventAssignment (name, mod)`
Event assignments are actions that are triggered by an event. Ported from Core2 to build an event handling framework fro PySCeS

```
code_string = None
evaluateAssignment ()
formula = None
mod = None
piecewises = None
setFormula (formula)
setVariable (var)
symbols = None
variable = None
xcode = None
```

class `pysces.PyscesModel.Function (name, mod)`
Function class ported from Core2 to enable the use of functions in PySCeS.

```
addFormula (formula)
args1 = None
code_string = None
formula = None
functions = None
mod = None
piecewises = None
setArg (var, value=None)
```

symbols = None

value = None

xcode = None

class `pysces.PyscesModel.IntegrationDataObj`

This class is specifically designed to store the results of a time simulation. It has methods for setting the Time, Labels, Species and Rate data and getting Time, Species and Rate (including time) arrays. However, of more use:

- `getOutput(*args)` feed this method species/rate labels and it will return an array of [time, sp1, r1, ...]
- `getDataAtTime(time)` the data generated at time point “time”.
- `getDataInTimeInterval(time, bounds=None)` more intelligent version of the above returns an array of all data points where: time-bounds <= time <= time+bounds

HAS_RATES = False

HAS_RULES = False

HAS_SPECIES = False

HAS_TIME = False

HAS_XDATA = False

IS_VALID = True

TYPE_INFO = ‘Deterministic’

getAllSimData (*lbls=False*)

Return all available data as time+species+rates+rules if *lbls=True* returns (array, labels) else just array

getDataAtTime (*time*)

Return all data generated at “time”

getDataInTimeInterval (*time, bounds=None*)

`getDataInTimeInterval(time, bounds=None)` returns an array of all data points where: time-bounds <= time <= time+bounds where bound defaults to stepsize

getOutput (**args, **kwargs*)

Old alias for `getSimData()` `getOutput(*args)` feed this method species/rate labels and it will return an array of [time, sp1, r1, ...]

getRates (*lbls=False*)

return time+rate array

getRules (*lbls=False*)

Return time+rule array

getSimData (**args, **kwargs*)

`getSimData(*args)` feed this method species/rate labels and it will return an array of [time, sp1, r1, ...]

getSpecies (*lbls=False*)
return time+species array

getTime (*lbls=False*)
return the time vector

getXData (*lbls=False*)
Return time+xdata array

rate_labels = None

rates = None

rules = None

rules_labels = None

setLabels (*species=None, rates=None, rules=None*)
set the species, rate and rule label lists

setRates (*rates, lbls=None*)
set the rate array

setRules (*rules, lbls=None*)
Set the results of rate rules

setSpecies (*species, lbls=None*)
Set the species array

setTime (*time, lbl=None*)
Set the time vector

setXData (*xdata, lbls=None*)
Sets extra simulation data

species = None

species_labels = None

time = None

time_label = 'Time'

xdata = None

xdata_labels = None

class `pysces.PyscesModel.NewCoreBase`
Core2 base class, needed here as we use Core2 derived classes in PySCes

get (*attr*)
Return an attribute whose name is str(attr)

getName ()

name = None

setName (*name*)

class `pysces.PyscesModel.NumberBase`

Derived Core2 number class.

getValue ()

setValue (*v*)

value = None

value_initial = None

class `pysces.PyscesModel.PieceWise` (*pwd, mod*)

Generic piecewise class adapted from Core2 that generates a compiled Python code block that allows evaluation of arbitrary length piecewise functions. Piecewise statements should be defined in assignment rules as *piecewise*(*<Piece>*, *<Conditional>*, *<Other-Value>*) where there can be an arbitrary number of *<Piece>*, *<Conditional>* pairs.

- args* a dictionary of piecewise information generated by the InfixParser as InfixParser.piecewises

code_string = None

formula = None

name = None

value = None

xcode = None

class `pysces.PyscesModel.PysMod` (*File=None, dir=None, loader='file', fString=None, autoload=True*)

Create a model object and instantiate a PySCeS model so that it can be used for further analyses. PySCeS model descriptions can be loaded from files or strings (see the *loader* argument for details).

- File* the name of the PySCeS input file if not explicit a *.psc extension is assumed.
- dir* if specified, the path to the input file otherwise the default PyscesModel directory (defined in the `pys_config.ini` file) is assumed.
- autoload* autoload the model, pre 0.7.1 call `mod.doLoad()`. (default=True) **new**
- loader* the default behaviour is to load PSC file, however, if this argument is set to 'string' an input file can be supplied as the *fString* argument (default='file')
- fString* a string containing a PySCeS model file (use with *loader='string'*) the *File* argument now specifies the new input file name.

CVODE (*initial*)

PySCeS interface to the CVODE integration algorithm.

Arguments: *initial*: vector containing initial species concentrations

CVODE_EVENTS (*t, svec, eout, f_data*)

CVODE_VPYTHON (*s*)

Future VPython hook for CVODE

CVODE_continue (*tvec*)

Experimental: continues a simulation over a new time vector, the CVODE memobj is reused and not reinitialised and model parameters can be changed between calls to this method. The `mod.data_sim` objects from the initial simulation and all calls to this method are stored in the list `mod.CVODE_continuous_result`.

- tvec* a numpy array of time points

CVODE_continuous_result = None

CleanNaNsFromArray (*arr, replace_val=0.0*)

Scan a matrix for NaN's and replace with zeros:

- arr* the array to be cleaned

EvalCC ()

Calculate the MCA control coefficients using the current steady-state solution.

`mod.__settings__[\"mca_ccj_upsymb\"] = 1` attach the flux control coefficients to the model instance
`mod.__settings__[\"mca_ccs_upsymb\"] = 1` attach the concentration control coefficients to the model instance

Arguments: None

EvalEigen ()

Calculate the eigenvalues or vectors of the unscaled Jacobian matrix and thereby analyse the stability of a system

Arguments: None

EvalEpar (*input=None, input2=None*)

Calculate reaction elasticities towards the parameters.

Both inputs (`input1=species, input2=rates`) should be valid (steady state for MCA) solutions and given in the correct order for them to be used. If either or both are missing the last state values are used automatically. Elasticities are scaled using input 1 and 2.

Arguments:

- `input` [default=None]: species concentration vector
- `input2` [default=None]: reaction rate vector

Settings, set in `mod.__settings__`:

<pre>- elas_epar_upsymb [default = 1] attach individual elasticity symbols - elas_scaling_div0_fix [default=False] if NaN's are detected in the var</pre>

EvalEvar (*input=None, input2=None*)

Calculate reaction elasticities towards the variable species.

Both inputs (`input1=species, input2=rates`) should be valid (steady state for MCA) solutions and given in the correct order for them to be used. If either or both are missing the last state values are used automatically. Elasticities are scaled using input 1 and 2.

Arguments:

- input [default=None]: species concentration vector
- input2 [default=None]: reaction rate vector

Settings, set in mod.__settings__:

- elas_evar_upsymb [default = 1] attach individual elasticity symbols
- elas_zero_conc_fix [default=False] if zero concentrations are detected
- elas_zero_flux_fix [default=False] if zero fluxes are detected in a st
- elas_scaling_div0_fix [default=False] if INF's are detected after scal

EvalRC ()

Calculate the MCA response coefficients using the current steady-state solution.

Arguments: None

EvalRCT ()

Calculate the MCA response coefficients using the current steady-state solution.

Responses to changes in the sums of moiety conserved cycles are also calculated.

Arguments: None

FINTSLV (initial)

Forward integration steady-state solver. Finds a steady state when the maximum change in species concentration falls within a specified tolerance. Returns the steady-state solution and a error flag. Algorithm controls are available as mod.fintslv_<control>

Arguments:

initial: vector of initial concentrations

Fix_S_fullinput (s_vec)

Using the full concentration vector evaluate the dependent species

Arguments:

s_vec: a full length concentration vector

Fix_S_indinput (s_vec, amounts=True)

whether to use self.__tvec_a__ (default) or self.__tvec_c__

Given a vector of independent species evaluate and return a full concentration vector.

Arguments:

s_vec: vector of independent species

Fix_Sim (metab, flux=0, par=0)

Deprecated

FluxGenSim (s)

Deprecated

Forcing_Function ()

User defined forcing function either defined in the PSC input file as !F or by overwriting this method. This method is evaluated prior to every rate equation evaluation.

Arguments: None

HYBRD (*initial*)

PySCeS interface to the HYBRD solver. Returns a steady-state solution and error flag. Good general purpose solver. Algorithm controls are available as `mod.hybrd_<control>`

Arguments:

initial: vector of initial species concentrations

InitialiseCompartments ()

InitialiseConservationArrays ()

Initialise conservation related vectors/array was in `InitialiseModel` but has been moved out so is can be called by when the stoichiometry is reanalysed

InitialiseEvents ()

InitialiseFunctions ()

InitialiseInputFile ()

Parse the input file associated with the PySCeS model instance and assign the basic model attributes

Arguments: None

InitialiseModel ()

Initialise and set up dynamic model attributes and methods using the model defined in the associated PSC file

Arguments: None

InitialiseOldFunctions ()

Parse and initialise user defined functions specified by !T !U in the PSC input file

Arguments: None

InitialiseRuleChecks ()

InitialiseRules ()

LSODA (*initial*)

PySCeS interface to the LSODA integration algorithm. Given a set of initial conditions LSODA returns an array of species concentrations and a status flag. LSODA controls are accessible as `mod.lsoda_<control>`

Arguments:

initial: vector containing initial species concentrations

LoadFromFile (*File=None, dir=None*)

`__init__`(File=None,dir=None)

Initialise a PySCeS model object with PSC file that can be found in optional directory. If a filename is not supplied the pysces.model_dir directory contents is displayed and the model name can be entered at the prompt (<ctrl>+C exits the loading process).

Arguments:

File [default=None]: the name of the PySCeS input file
 dir [default=pysces.model_dir]: the optional directory where the PSC file can be found

LoadFromString (*File=None, fString=None*)

Docstring required

ModelLoad (*stoich_load=0*)

Load and instantiate a PySCeS model so that it can be used for further analyses. This function replaces the pre-0.7.1 doLoad() method.

- stoich_load* try to load a structural analysis saved with Stoichiometry_Save_Serial() (default=0)

NLEQ2 (*initial*)

PySCeS interface to the (optional) NLEQ2 algorithm. This is a powerful steady-state solver that can usually find a solution for when HYBRD() fails. Algorithm controls are available as: mod.nleq2_<control> Returns as steady-state solution and error flag.

Arguments:

initial: vector of initial species concentrations

PITCON (*scanpar, scanpar3d=None*)

PySCeS interface to the PITCON continuation algorithm. Single parameter continuation has been implemented as a “scan” with the continuation being initialised in mod.pitcon_par_space. The second argument does not affect the continuation but can be used to insert a third axis parameter into the results. Returns an array containing the results. Algorithm controls are available as mod.pitcon_<control>

Arguments:

scanpar: the model parameter to scan (x5)
 scanpar3d [default=None]: additional output parameter for 3D plots

ParGenSim ()

Deprecated

ReloadInitFunc ()

Recompile and execute the user initialisations (!I) as defined in the PSC input file. and in mod.__InitFuncs__.

UPDATE 2015: can now be used to define InitialAssignments (no need for self.* prefix in input file)

Arguments: None

ReloadUserFunc ()

Recompile and execute the user function (!U) from the input file.

Arguments: None

ResetNumberFormat ()

Reset PySCeS default number format stored as mod.mode_number format to %2.4e

Arguments: None

ScaleKL (*input*, *input2*)

Scale the K and L matrices with current steady state (if either input1 or 2 == None) or user input.

Arguments:

input: vector of species concentrations input2: vector of reaction rates

Scan1 (*range1*=[], *runUF*=0)

Perform a single dimension parameter scan using the steady-state solvers. The parameter to be scanned is defined (as a model attribute “P”) in mod.scan_in while the required output is entered into the list mod.scan_out. Results of a parameter scan can be easily viewed with Scan1Plot().

mod.scan_in - a model attribute written as in the input file (eg. P, Vmax1 etc) mod.scan_out - a list of required output ['A','T2', 'ecR1_s1', 'ccJR1_R1', 'rcJR1_s1', ...] mod.scan_res - the results of a parameter scan mod.scan - numpy record array with the scan results (scan_in and scan_out), call as mod.scan.Vmax, mod.scan.A_ss, mod.scan.J_R1, etc. mod.__settings__[“scan1_mca_mode”] - force the scan algorithm to evaluate the elasticities (1) and control coefficients (2) (this should also be auto-detected by the Scan1 method).

Arguments:

range1 [default=[]]: a predefined range over which to scan. runUF [default=0]: run (1) the user defined function mod.User_Function (!U) before evaluating the steady state.

Scan1Plot (*plot*=[], *title*=None, *log*=None, *format*='lines', *filename*=None)

Plot the results of a parameter scan generated with **Scan1()**

- *plot* if empty mod.scan_out is used, otherwise any subset of mod.scan_out (default=[])
- *filename* the filename of the PNG file (default=None, no export)
- *title* the plot title (default=None)
- *log* if None a linear axis is assumed otherwise one of ['x','xy','xyz'] (default=None)
- *format* the backend dependent line format (default='lines') or the *Common-Style* 'lines' or 'points'.

Scan2D (*p1*, *p2*, *output*, *log*=False)

Generate a 2 dimensional parameter scan using the steady-state solvers.

- *p1* is a list of [parameter1, start, end, points]
- *p2* is a list of [parameter2, start, end, points]
- *output* steady-state variable/properties e.g. 'J_R1', 'A_ss', 'ecR1_s1'
- *log* scan using log ranges for both axes

Scan2DPlot (*title=None, log=None, format='lines', filename=None*)

Plot the results of a 2D scan generated with Scan2D

- *filename* the filename of the PNG file (default=None, no export)
- *title* the plot title (default=None)
- *log* if None a linear axis is assumed otherwise one of ['x','xy','xyz'] (default=None)
- *format* the backend dependent line format (default='lines') or the *Common-Style* 'lines' or 'points'.

SerialDecode (*filename*)

Decode and return a serialised object saved with SerialEncode.

Arguments:

filename: the filename (.pscdat is assumed)

SerialEncode (*data, filename*)

Serialise and save a Python object using a binary pickle to file. The serialised object is saved as <filename>.pscdat in the directory defined by mod.model_serial.

Arguments:

data: pickleable Python object filename: the output filename

SetLoud ()

Turn on as much solver reporting noise as possible:
 mod.__settings__['hybrd_mesg'] = 1 mod.__settings__['nleq2_mesg'] = 1
 mod.__settings__['lsoda_mesg'] = 1 mod.__settings__['mode_state_mesg'] = 1
 mod.__settings__['solver_switch_warning'] = True

Arguments: None

SetQuiet ()

Turn off as much solver reporting noise as possible:
 mod.__settings__['hybrd_mesg'] = 0 mod.__settings__['nleq2_mesg'] = 0
 mod.__settings__['lsoda_mesg'] = 0 mod.__settings__['mode_state_mesg'] = 0
 mod.__settings__['solver_switch_warning'] = False

Arguments: None

SetStateSymb (*flux, metab*)

Sets the individual steady-state flux and concentration attributes as mod.J_<reaction> and mod.<species>_ss

Arguments:

flux: the steady-state flux array
metab: the steady-state concentration array

SimPlot (*plot='species', filename=None, title=None, log=None, format='lines'*)

Plot the simulation results, uses the new UPI `pysces.plt` interface:

- *plot*: output to plot (default='species')
- 'all' rates and species
- 'species' species
- 'rates' reaction rates
- [*'SI', 'RI',]* a list of model attributes (species, rates)
- *filename* if not None file is exported to filename (default=None)
- *title* the plot title (default=None)
- *log* use log axis for 'x', 'y', 'xy' (default=None)
- *format* line format, backend dependant (default='')

Simulate (*userinit=0*)

PySCeS integration driver routine that evolves the system over the time. Resulting array of species concentrations is stored in the **mod.data_sim** object Initial concentrations can be selected using *mod.__settings__['mode_sim_init']* (default=0):

- 0 initialise with initial concentrations
- 1 initialise with a very small (close to zero) value
- 2 initialise with results of previously calculated steady state
- 3 initialise with final point of previous simulation

userinit values can be (default=0):

- 0: initial species concentrations initialised from (`mod.S_init`), time array calculated from `sim_start/sim_end/sim_points`
- 1: initial species concentrations initialised from (`mod.S_init`) existing "`mod.sim_time`" used directly
- 2: initial species concentrations read from "`mod.__inspec__`", "`mod.sim_time`" used directly

State ()

PySCeS non-linear solver driver routine. Solve for a steady state using HYBRD/NLEQ2/FINTSLV algorithms. Results are stored in `mod.state_species` and `mod.state_flux`. The results of a steady-state analysis can be viewed with the `mod.showState()` method.

The solver can be initialised in 3 ways using the `mode_state_init` switch. `mod.mode_state_init = 0` initialize with species initial values `mod.mode_state_init`

= 1 initialize with small values mod.mode_state_init = 2 initialize with the final value of a 10-logstep simulation `numpy.logspace(0,5,18)`

Arguments: None

Stoich_nmatrix_SetValue (*species, reaction, value*)

Change a stoichiometric coefficient's value in the N matrix. Only a coefficient's magnitude may be set, in other words a coefficient's value must remain negative, positive or zero. After changing a coefficient it is necessary to Reanalyse the stoichiometry.

Arguments:

species: species name (s0) reaction: reaction name (R4) value: new coefficient value

Stoichiometry_Analyse (*override=0, load=0*)

Perform a structural analyses. The default behaviour is to construct and analyse the model from the parsed model information. Overriding this behaviour analyses the stoichiometry based on the current stoichiometric matrix. If load is specified PySCeS tries to load a saved stoichiometry, otherwise the stoichiometric analysis is run. The results of the analysis are checked for floating point error and nullspace rank consistency.

Arguments:

override [default=0]: override stoichiometric analysis intialisation from parsed data
load [default=0]: load a presaved stoichiometry

Stoichiometry_Init (*nmatrix, load=0*)

Initialize the model stoichiometry. Given a stoichiometric matrix N, this method will return an instantiated PyscesStoich instance and status flag. Alternatively, if load is enabled, PySCeS will attempt to load a previously saved stoichiometric analysis (saved with `Stoichiometry_Save_Serial`) and test it's correctness. The status flag indicates 0 = reanalyse stoichiometry or 1 = complete structural analysis preloaded.

Arguments:

nmatrix: The input stoichiometric matrix, N load [default=0]: try to load a saved stoichiometry (1)

Stoichiometry_Load_Serial ()

Load a saved stoichiometry saved with `mod.Stoichiometry_Save_Serial()` and return a stoichiometry instance.

Arguments: None

Stoichiometry_ReAnalyse ()

Reanalyse the stoichiometry using the current N matrix ie `override=1` (for use with `mod.Stoich_matrix_SetValue`)

Arguments: None

Stoichiometry_Save_Serial()

Serialize and save a Stoichiometric instance to binary pickle `Stoichiometry_Save_Serial()`

Serialize and save the current model stoichiometry to a file with name `<model>_stoichiometry.pscdat` in the `mod.__settings__['serial_dir']` directory (default: `mod.model_output/pscdat`)

Arguments: None

TestSimState (*endTime=10000, points=101, diff=1e-05*)

Deprecated

User_Function()

Deprecated

Write_array (*input, File=None, Row=None, Col=None, close_file=0, separator=' '*)

Write an array to `File` with optional row/col labels. A `' '` separator can be specified to create a CSV style file.

`mod.__settings__['write_array_header']`: add `<filename>` as a header line (1 = yes, 0 = no) `mod.__settings__['write_array_spacer']`: add a space after the header line (1 = yes, 0 = no) `mod.__settings__['write_arr_lflush']`: set the flush rate for large file writes

Arguments:

`input`: the array to be written `File` [default=None]: an open, writable Python file object `Row` [default=None]: a list of row labels `Col` [default=None]: a list of column labels `close_file` [default=0]: close the file after write (1) or leave open (0) `separator` [default=' ']: the column separator to use

Write_array_html (*input, File=None, Row=None, Col=None, name=None, close_file=0*)

Write an array as an HTML table (no header/footer) or complete document. Tables are formatted with coloured columns if they exceed a specified size.

`mod.__settings__['write_array_html_header']`: write the HTML document header `mod.__settings__['write_array_html_footer']`: write the HTML document footer

Arguments:

`input`: the array to be written `File` [default=None]: an open, writable Python file object `Row` [default=None]: a list of row labels `Col` [default=None]: a list of column labels `name` [default=None]: an HTML table description line `close_file` [default=0]: close the file after write (1) or leave open (0)

Write_array_latex (*input, File=None, Row=None, Col=None, close_file=0*)

Write an array to an open file as a 'LaTeX' {array}

Arguments:

`input`: the array to be written `File` [default=None]: an open, writable Python file object `Row` [default=None]: a list of row labels `Col` [default=None]: a list of column

labels close_file [default=0]: close the file after write (1) or leave open (0)

clone ()

Returns a deep copy of this model object (experimental!)

doEigen ()

Calculate the eigenvalues, automatically performs a steady state and elasticity analysis.

Calls: State() EvalEvar() Evaleigen()

Arguments: None

doEigenMca ()

Calculate a full Control Analysis and eigenvalues, automatically performs a steady state, elasticity, control analysis.

Calls: State() EvalEvar() EvalCC() Evaleigen()

Arguments: None

doEigenShow ()

Calculate the eigenvalues, automatically performs a steady state and elasticity analysis and displays the results.

Calls: doEigen() showEigen()

Arguments: None

doElas ()

Calculate the model elasticities, this method automatically calculates a steady state.

Calls: State() EvalEvar() EvalEpar()

Arguments: None

doLoad (stoich_load=0)

Load and instantiate a PySCeS model so that it can be used for further analyses. This function is being replaced by the ModelLoad() method.

- *stoich_load* try to load a structural analysis saved with Stoichiometry_Save_Serial() (default=0)

doMca ()

Perform a complete Metabolic Control Analysis on the model, automatically calculates a steady state.

Calls: State() EvalEvar() EvalEpar() EvalCC()

Arguments: None

doMcaRC ()

doMca()

Perform a complete Metabolic Control Analysis on the model, automatically calculates a steady state.

Calls: State() EvalEvar() EvalEpar() EvalCC() EvalRC()

Arguments: None

doMcaRCT ()

Perform a complete Metabolic Control Analysis on the model, automatically calculates a steady state.

In additional, response coefficients to the sums of moiety-conserved cycles are calculated.

Calls: State() EvalEvar() EvalEpar() EvalCC() EvalRC() EvalRCT()

Arguments: None

doSim (*end=10.0, points=20.0*)

Run a time simulation from t=0 to t=sim_end with sim_points.

Calls: Simulate()

Arguments:

end [default=10.0]: simulation end time *points* [default=20.0]: number of points in the simulation

doSimPerturb (*pl, end*)

Deprecated: use events instead

doSimPlot (*end=10.0, points=21, plot='species', fmt='lines', filename=None*)

Run a time simulation from t=0 to t=sim_end with sim_points and plot the results.

The required output data and format can be set:

- *end* the end time (default=10.0)
- *points* the number of points in the simulation (default=20.0)
- *plot* (default='species') select output data
 - 'species'
 - 'rates'
 - 'all' both species and rates
- *fmt* plot format, UPI backend dependent (default='') or the *CommonStyle* 'lines' or 'points'.
- *filename* if not None (default) then the plot is exported as *filename.png*

Calls: - **Simulate**() - **SimPlot**()

doState ()

Calculate the steady-state solution of the system.

Calls: State()

Arguments: None

doStateShow ()

Calculate the steady-state solution of a system and show the results.

Calls: State() showState()

Arguments: None

```
exportSimAsSedML (output='files', return_sed=False, vc_given='PySCeS',  

                 vc_family='Software', vc_email='',  

                 vc_org='pysces.sourceforge.net')
```

Exports the current simulation as SED-ML in various ways it creates and stores the SED-ML files in a folder generated from the model name.

- *output* [default='files'] the SED-ML export type can be one or more comma separated e.g. 'files,combine'
- *files* export the plain SBML and SEDML XML files
- *archive* export as a SED-ML archive *<file>.sedx* containing the SBML and SEDML xml files
- *combine* export as a COMBINE archive *<file>.omex* containing the SBML, SEDML, manifest (XML) and metadata (RDF)
 - *vc_given* [default='PySCeS'] - *vc_family* [default='Software']
 - *vc_email* [default='bgoli@users.sourceforge.net'] - *vc_org* [default='<pysces.sourceforge.net>']

scan

showCC (*File=None*)

Print all control coefficients as 'LaTeX' formatted strings to the screen or file.

Arguments:

File [default=None]: an open, writable Python file object

showConserved (*File=None, screenwrite=1, fmt='%2.3f'*)

Print the moiety conserved cycles present in the system.

Arguments:

File [default=None]: an open writable Python file object screenwrite [default=1]: write results to console (0 means no response) fmt [default='%2.3f']: the output number format string

showEigen (*File=None*)

Print the eigenvalues and stability analysis of a system generated with EvalEigen() to the screen or file.

Arguments:

File [default=None]: an open, writable Python file object

showElas (*File=None*)

Print all elasticities to screen or file as 'LaTeX' compatible strings. Calls showEvar() and showEpar()

Arguments:

File [default=None]: an open writable Python file object

showEpar (*File=None*)

Write out all nonzero parameter elasticities as ‘LaTeX’ formatted strings, alternatively write to file.

Arguments:

File [default=None]: an open writable Python file object

showEvar (*File=None*)

Write out all variable elasticities as ‘LaTeX’ formatted strings, alternatively write results to a file.

Arguments:

File [default=None]: an open writable Python file object

showFluxRelationships (*File=None*)

showConserved(*File=None*)

Print the flux relationships present in the system.

Arguments:

File [default=None]: an open writable Python file object

showK (*File=None, fmt='%2.3f'*)

Print the Kernel matrix (K), including row and column labels to screen or File.

Arguments:

File [default=None]: an open, writable Python file object *fmt* [default='%2.3f']: output number format

showL (*File=None, fmt='%2.3f'*)

Print the Link matrix (L), including row and column labels to screen or File.

Arguments:

File [default=None]: an open, writable Python file object *fmt* [default='%2.3f']: output number format

showModel (*filename=None, filepath=None, skipcheck=0*)

The PySCeS ‘save’ command, prints the entire model to screen or File in a PSC format. (Currently this only applies to basic model attributes, ! functions are not saved).

Arguments:

filename [default=None]: the output PSC file *filepath* [default=None]: the output directory *skipcheck* [default=0]: skip check to see if the file exists (1) auto-averwrite

showModifiers (*File=None*)

Prints the current value of the model’s modifiers per reaction to screen or file.

Arguments:

File [default=None]: an open, writable Python file object

showN (*File=None, fmt='%2.3f'*)

Print the stoichiometric matrix (N), including row and column labels to screen or File.

Arguments:

File [default=None]: an open, writable Python file object
fmt [default='%2.3f']: output number format

showNr (*File=None, fmt='%2.3f'*)

Print the reduced stoichiometric matrix (Nr), including row and column labels to screen or File.

Arguments:

File [default=None]: an open, writable Python file object
fmt [default='%2.3f']: output number format

showODE (*File=None, fmt='%2.3f'*)

Print a representation of the full set of ODE's generated by PySCeS to screen or file.

Arguments:

File [default=None]: an open, writable Python file object
fmt [default='%2.3f']: output number format

showODEr (*File=None, fmt='%2.3f'*)

Print a representation of the reduced set of ODE's generated by PySCeS to screen or file.

Arguments:

File [default=None]: an open, writable Python file object
fmt [default='%2.3f']: output number format

showPar (*File=None*)

Prints the current value of the model's parameter values (mod.P) to screen or file.

Arguments:

File [default=None]: an open, writable Python file object

showRate (*File=None*)

Prints the current rates of all the reactions using the current parameter values and species concentrations

•File an open, writable Python file object (default=None)

showRateEq (*File=None*)

Prints the reaction stoichiometry and rate equations to screen or File.

Arguments:

File [default=None]: an open, writable Python file object

showSpecies (*File=None*)

Prints the current value of the model's variable species (mod.X) to screen or file.

Arguments:

File [default=None]: an open, writable Python file object

showSpeciesFixed (*File=None*)

Prints the current value of the model's fixed species values (mod.X) to screen or file.

Arguments:

File [default=None]: an open, writable Python file object

showSpeciesI (*File=None*)

Prints the current value of the model's variable species initial values (mod.X_init) to screen or file.

Arguments:

File [default=None]: an open, writable Python file object

showState (*File=None*)

Prints the result of the last steady-state analyses. Both steady-state flux's and species concentrations are shown.

Arguments:

File [default=None]: an open, writable Python file object

class `pysces.PyscesModel.ReactionObj` (*mod, name, kl, klrepl='self.'*)

Defines a reaction with a KineticLaw *kl*, **formula* and *name* bound to a model instance, *mod*.

code_string = None

compartment = None

formula = None

mod = None

piecewises = None

rate = None

setKineticLaw (*kl, klrepl='self.'*)

symbols = None

xcode = None

class `pysces.PyscesModel.ScanDataObj` (*par_label*)

New class used to store parameter scan data (uses StateDataObj)

ALL_VALID = True

HAS_FLUXES = False

HAS_MOD_DATA = False

HAS_RULES = False

```
HAS_SET_LABELS = False
HAS_SPECIES = False
HAS_XDATA = False
OPEN = True
addModData (mod, *args)
addPoint (ipar, ssdata)
    takes a list/array of input parameter values and the associated ssdata object
closeScan ()
flux_labels = None
fluxes = None
getAllScanData (lbls=False)
getFluxes (lbls=False)
getModData (lbls=False)
getRules (lbls=False)
getScanData (*args, **kwargs)
    getScanData(*args) feed this method species/flux/rule/mod labels and it will return
    an array of [parameter(s), sp1, f1, ....]
getSpecies (lbls=False)
getXData (lbls=False)
invalid_states = None
mod_data = None
mod_data_labels = None
parameter_labels = None
parameters = None
rules = None
rules_labels = None
setLabels (ssdata)
species = None
species_labels = None
xdata = None
xdata_labels = None

class pysces.PyscesModel.StateDataObj
    New class used to store steady-state data.
```

HAS_FLUXES = False

HAS_RULES = False

HAS_SPECIES = False

HAS_XDATA = False

IS_VALID = True

flux_labels = None

fluxes = None

getAllStateData (*lbls=False*)

Return all available data as species+fluxes+rules if *lbls=True* returns (array,labels)
else just array

getFluxes (*lbls=False*)

return flux array

getRules (*lbls=False*)

Return rule array

getSpecies (*lbls=False*)

return species array

getStateData (**args, **kwargs*)

`getSimData(*args)` feed this method species/rate labels and it will return an array of
[time, sp1, r1,]

getXData (*lbls=False*)

Return xdata array

rules = None

rules_labels = None

setFluxes (*fluxes, lbls=None*)

set the flux array

setRules (*rules, lbls=None*)

Set the results of rate rules

setSpecies (*species, lbls=None*)

Set the species array

setXData (*xdata, lbls=None*)

Sets extra simulation data

species = None

species_labels = None

xdata = None

xdata_labels = None

class `pysces.PyscesModel.WasteManagement`

`pysces.PyscesModel.chkmdir()`

Import and grab `pysces.model_dir`

Arguments: None

`pysces.PyscesModel.chkpsc (File)`

Check whether the filename "File" has a '.psc' extension and adds one if not.

Arguments:

File: filename string

PYSCCESSCAN

PySCeS classes for continuations and multi-dimensional parameter scans

class `pysces.PyscesScan.PITCONScanUtils` (*model*)

Static Bifurcation Scanning utilities using PITCON, call with loaded model object. Hopefully nobody else was trying to use the older class as it was horrible. This new one is leaner, meaner and pretty cool ;-)

analyseData (*analysis='elas'*)

Performs “analysis” on the PITCON generated set of steady-state results where analysis is:

- ‘elasv’ = variable elasticities
- ‘elasp’ = parameter elasticities
- ‘elas’ = all elasticities
- ‘mca’ = control coefficients
- ‘resp’ = response coefficients
- ‘eigen’ = eigen values
- ‘all’ = all of the above

Higher level analysis types automatically enable the lower level analysis needed e.g. selecting ‘mca’ implies ‘elasv’ etc. User output defined with `mod.setUserOutput()` is stored in the `mod.res_user` array.

getArrayListAsArray (*array_list*)

Stack (concatenate) the list of arrays into a single array.

model = None

pitcon_range_high = None

pitcon_range_low = None

pitcon_res = None

pitcon_scan_density = None

pitcon_scan_parameter = None

pitcon_scan_parameter_3d = None

res_eigen = None

res_flux = None

res_idx = None

res_metab = None

res_user = None

runContinuation (*parameter, low, high, density, par3d=None, logrange=True, runQuiet=True*)

Run the continuation using the following parameters:

Args:

- parameter = str(the parameter to be scanned)
- low = float(lower bound)
- high = float(upper bound)
- density = int(the number of initial points)
- par3d = float(extra 3d parameter to insert into the output array) this parameter is not set ONLY used in output
- logrange = boolean [default = True], if True generate the result using logspace(log10(low), log10(high), density) otherwise use a linear range
- runQuiet = boolean [default = True], if True do not display intermediate results to screen, disable for debugging

After running the continuation the results are stored in numpy arrays

- mod.res_idx = scan parameter values (and optionally par3d)
- mod.res_metab = steady-state species concentrations
- mod.res_flux = steady-state flux values

setUserOutput (**args*)

Set the user output required as n string arguments.

timer = None

user_output = None

class pysces.PyscesScan.**Scanner** (*mod*)

Arbitrary dimension generic scanner. This class is initiated with a loaded PySCeS model and then allows the user to define scan parameters see self.addScanParameter() and user output see self.addUserOutput(). Steady-state results are always stored in self.SteadyStateResults while user output can be found in self.UserOutputResults - Brett 2007.

Analyze ()

The analysis method, the mode is automatically set by the self.addUserOutput() method but can be reset by the user.

HAS_STATE_OUTPUT = True

HAS_USER_OUTPUT = False

MSG_PRINT_INTERVAL = 500

Run (*ReRun=False*)

Run the parameter scan

RunAgain ()

While it is impossible to change the generator/range structure of a scanner (just build another one) you can ‘in principle’ change the User Output and run it again.

StoreData ()

Internal function which concatenates and stores the data generated by Analyze.

addScanParameter (*name, start, end, points, log=False, slave=False*)

Add a parameter to scan (an axis if you like) input is:

- str(name) = model parameter name
- float(start) = lower bound of scan
- float(end) = upper bound of scan
- int(points) = number of points in scan range
- bool(log) = Use a logarithmic (base10) range
- bool(slave) = Scan parameters can be masters i.e. an independent axis or a “slave” which moves synchronously with the previously defined parameter range.

The first ScanParameter cannot be a slave.

addUserOutput (**kw*)

Add output parameters to the scanner as a collection of one or more string arguments ('O1','O2','O3', 'On'). These are evaluated at each iteration of the scanner and stored in the self.UserOutputResults array. The list of output is stored in self.UserOutputList.

genOn = True

getOutput ()

Will be the new output function.

getResultMatrix (*stst=False, lbls=False*)

Returns an array of result data. I'm keepin this for backwards compatibility but it will be replaced by a getOutput() method when this scanner is updated to use the new data_scan object.

- stst* add steady-state data to output array
- lbls* return a tuple of (array, column_header_list)

If *stst* is True output has dimensions [scan_parameters]+[state_species+state_flux]+[Useroutput] otherwise [scan_parameters]+[Useroutput].

invalid_state_list = None

invalid_state_list_idx = None

makeRange (*start, end, points, log*)

Should be pretty self evident it defines a range:

- float(start)
- float(end)
- int(points)
- bool(log)

nan_on_bad_state = True

quietRun = False

rangeGen (*name, start, end, points, log*)

This is where things get more interesting. This function creates a cycling generator which loops over a parameter range.

- parameter name*
- start value*
- end value*
- points*
- log scale*

resetInputParameters ()

Just remembered what this does, I think it resets the input model parameters after a scan run.

setModValue (*name, value*)

An easy one, assign value to name of the instantiated PySCeS model attribute

stepGen (*offset*)

Another looping generator function. The idea here is to create a set of generators for the scan parameters. These generators then all fire together and determine whether the range generators should advance or not. Believe it or not this dynamically creates the matrix of parameter values to be evaluated.

testInputParameter (*name*)

This tests whether a str(name) is an attribute of the model

PYSCESINTERFACES

Interfaces converting to and from PySCeS models - makes use of Brett's Core2

class `pysces.PyscesInterfaces.Core2interfaces`

Defines interfaces for translating PySCeS model objects into and from other formats.

convertSBML2PSC (*sbmlfile*, *sbmdir=None*, *pscfile=None*, *pscdir=None*)

Convert an SBML file to a PySCeS MDL input file.

- *sbmlfile*: the SBML file name
- *sbmdir*: the directory of SBML files (if None current working directory is assumed)
- *pscfile*: the output PSC file name (if None *sbmlfile.psc* is used)
- *pscdir*: the PSC output directory (if None the `pysces.model_dir` is used)

core = None

core2psc = None

core2sbml = None

readMod2Core (*mod*, *iValues=True*)

Convert a PySCeS model object to core2

- *iValues*: if True then the models initial values are used (or the current values if False).

readSBMLToCore (*filename*, *directory=None*)

Reads the SBML file specified with filename and converts it into a core2 object `pysces.interface.core`

- *filename*: the SBML file
- *directory*: (optional) the SBML file directory None means try the current working directory

sbml = None

sbml2core = None

sbml_level = 2

sbml_version = 1

writeCore2PSC (*filename=None, directory=None, getstrbuf=False*)

Writes a Core2 object to a PSC file.

- filename*: writes <filename>.xml or <model_name>.xml if None
- directory*: (optional) an output directory
- getstrbuf*: if True a StringIO buffer is returned instead of writing to disk

writeCore2SBML (*filename=None, directory=None, getdocument=False*)

Writes Core2 object to an SBML file.

- filename*: writes <filename>.xml or <model_name>.xml if None
- directory*: (optional) an output directory
- getdocument*: if True an SBML document object is returned instead of writing to disk or

writeMod2PSC (*mod, filename=None, directory=None, iValues=True, getstrbuf=False*)

Writes a PySCeS model object to a PSC file.

- filename*: writes <filename>.psc or <model_name>.psc if None
- directory*: (optional) an output directory
- iValues*: if True then the models initial values are used (or the current values if False).
- getstrbuf*: if True a StringIO buffer is returned instead of writing to disk

writeMod2SBML (*mod, filename=None, directory=None, iValues=True, getdocument=False, getstrbuf=False*)

Writes a PySCeS model object to an SBML file.

- filename*: writes <filename>.xml or <model_name>.xml if None
- directory*: (optional) an output directory
- iValues*: if True then the models initial values are used (or the current values if False).
- getdocument*: if True an SBML document object is returned instead of writing to disk or
- getstrbuf*: if True a StringIO buffer is returned instead of writing to disk

PYSCESSTOICH

PySCeS stoichiometric analysis classes.

class `pysces.PyscesStoich.MathArrayFunc`

PySCeS array functions - used by Stoich

LinAlgError = 'LinearAlgebraError'

MatrixFloatFix (*mat*, *val=1.e-15*)

Clean an array removing any floating point artifacts defined as being smaller than a specified value. Processes an array inplace

Arguments:

mat: the input 2D array *val* [default=1.e-15]: the threshold value (effective zero)

MatrixValueCompare (*matrix*)

Finds the largest/smallest $\text{abs}(\text{value}) > 0.0$ in a matrix. Returns a tuple containing (smallest,largest) values

Arguments:

matrix: the input 2D array

SwapCol (*res_a*, *r1*, *r2*)

Swap two columns using BLAS swap, arrays can be (or are upcast to) type double (d) or double complex (D). Returns the colswapped array

Arguments:

res_a: the input array *r1*: the first column to be swapped *r2*: the second column to be swapped

SwapCold (*res_a*, *c1*, *c2*)

Swaps two double (d) columns in an array using BLAS DSWAP. Returns the colswapped array.

Arguments:

res_a: input array *c1*: column index 1 *c2*: column index 2

SwapColz (*res_a*, *c1*, *c2*)

Swaps two double complex (D) columns in an array using BLAS ZSWAP. Returns the colswapped array.

Arguments:

res_a: input array c1: column index 1 c2: column index 2

SwapElem (*res_a, r1, r2*)

Swaps two elements in a 1D vector

Arguments:

res_a: the input vector r1: index 1 r2: index 2

SwapRow (*res_a, r1, r2*)

Swaps two rows using BLAS swap, arrays can be (or are upcast to) type double (d) or double complex (D). Returns the rowswapped array.

Arguments:

res_a: the input array r1: the first row index to be swapped r2: the second row index to be swapped

SwapRowd (*res_a, c1, c2*)

Swaps two double (d) rows in an array using BLAS DSWAP. Returns the rowswapped array.

Arguments:

res_a: input array c1: row index 1 c2: row index 2

SwapRowz (*res_a, c1, c2*)

Swaps two double complex (D) rows in an array using BLAS ZSWAP. Returns the rowswapped array.

Arguments:

res_a: input array c1: row index 1 c2: row index 2

array_kind = {'d': 0, 'F': 1, 'i': 0, 'f': 0, 'l': 0, 'D': 1}

array_precision = {'d': 1, 'F': 0, 'i': 1, 'f': 0, 'l': 1, 'D': 1}

array_type = [['f', 'd'], ['F', 'D']]

assertRank2 (**arrays*)

Check that we are using a 2D array

Arguments:

*arrays: input array(s)

castCopyAndTranspose (*type, *arrays*)

Cast numeric arrays to required type and transpose

Arguments:

type: the required type to cast to *arrays: the arrays to be processed

commonType (**arrays*)

Numeric detect and set array precision (will be replaced with new scipy.core compatible code when ready)

Arguments:

*arrays: input arrays

class `pysces.PyscesStoich.Stoich` (*input*)

PySCeS stoichiometric analysis class: initialized with a stoichiometric matrix N (input)

AnalyseK ()

Evaluate the stoichiometric matrix and calculate the nullspace using LU decomposition and backsubstitution . Generates the MCA K and Ko arrays and associated row and column vectors

Arguments: None

AnalyseL ()

Evaluate the stoichiometric matrix and calculate the left nullspace using LU factorization and backsubstitution. Generates the MCA L, Lo, Nr and Conservation matrix and associated row and column vectors

Arguments: None

BackSubstitution (*res_a, row_vector, column_vector*)

Jordan reduction of a scaled upper triangular matrix. The returned array is now in the form [I R] and can be used for nullspace determination. Modified row and column tracking vectors are also returned.

Arguments:

res_a: unitary pivot upper triangular matrix *row_vector*: row tracking vector *column_vector*: column tracking vector

GetUpperMatrix (*a*)

Core analysis algorithm; an input is preconditioned using `PivotSort_initial` and then cycles of `PLUfactorize` and `PivotSort` are run until the factorization is completed. During this process the matrix is reordered by column swaps which emulates a full pivoting LU factorization. Returns the pivot matrix P, upper factorization U as well as the row/col tracking vectors.

Arguments:

a: a stoichiometric matrix

GetUpperMatrixUsingQR (*a*)

`GetUpperMatrix(a)`

Core analysis algorithm; an input is preconditioned using `PivotSort_initial` and then cycles of `PLUfactorize` and `PivotSort` are run until the factorization is completed. During this process the matrix is reordered by column swaps which emulates a full pivoting LU factorization. Returns the pivot matrix P, upper factorization U as well as the row/col tracking vectors.

Arguments:

a: a stoichiometric matrix

K_split_R (*R_a, row_vector, column_vector*)

Using the R factorized form of the stoichiometric matrix we now form the K and Ko matrices. Returns the r_ipart,Komatrix,Krow,Kcolumn,Kmatrix,Korow,info

Arguments:

R_a: the Gauss-Jordan reduced stoichiometric matrix row_vector: row tracking vector column_vector: column tracking vector

L_split_R (*Nfull, R_a, row_vector, column_vector*)

Takes the Gauss-Jordan factorized N^T and extract the L, Lo, conservation (I - Lo) and reduced stoichiometric matrices. Returns: lmatrix_col_vector, lomatrix, lomatrix_row, lomatrix_co, nrmatrix, Nred_vector_row, Nred_vector_col, info

Arguments:

Nfull: the original stoichiometric matrix N R_a: gauss-jordan factorized form of N^T row_vector: row tracking vector column_vector: column tracking vector

PLUfactorize (*a_in*)

Performs an LU factorization using LAPACK D/ZGtrf. Now optimized for FLAPACK interface. Returns LU - combined factorization, IP - rowswap information and info - Gtrf error control.

Arguments:

a_in: the matrix to be factorized

PivotSort (*a, row_vector, column_vector*)

This is a sorting routine that accepts a matrix and row/column vectors and then sorts them so that: there are no zero rows (by swapping with first non-zero row) The abs(largest) pivots are moved onto the diagonal to maintain numerical stability. Row and column swaps are recorded in the tracking vectors.

Arguments:

a: the input array row_vector: row tracking vector column_vector: column tracking vector

PivotSort_initial (*a, row_vector, column_vector*)

This is a sorting routine that accepts a matrix and row/column vectors and then sorts them so that: the abs(largest) pivots are moved onto the diagonal to maintain numerical stability i.e. the matrix diagonal is in descending max(abs(value)). Row and column swaps are recorded in the tracking vectors.

Arguments:

a: the input array row_vector: row tracking vector column_vector: column tracking vector

SVD_Rank_Check (*matrix=None, factor=1.0e4, resultback=0*)

Calculates the dimensions of L/L0/K/K) by way of SVD and compares them to the Gauss-Jordan results. Please note that for LARGE ill conditioned matrices the SVD can become numerically unstable when used for nullspace determinations

Arguments:

matrix [default=None]: the stoichiometric matrix default is self.Nmatrix factor [default=1.0e4]: factor used to calculate the 'zero pivot' mask = mach_eps*factor resultback [default=0]: return the SVD results, U, S, vh

ScalePivots (*a_one*)

Given an upper triangular matrix U, this method scales the diagonal (pivot values) to one.

Arguments:

a_one: an upper triangular matrix U

SplitLU (*plu, row, col, t*)

PLU takes the combined LU factorization computed by PLUfactorize and extracts the upper matrix. Returns U.

Arguments:

plu: LU factorization row: row tracking vector col: column tracking vector t [default=None]): typecode argument (currently not used)

USE_QR = False

info_moiety_conserve = False

class pysces.PyscesStoich.**StructMatrix** (*array, ridx, cidx, row=None, col=None*)

This class is specifically designed to store structural matrix information give it an array and row/col index permutations it can generate its own row/col labels given the label src.

array = None

cidx = None

col = None

getByIdx (*row, col*)

getByName (*row, col*)

getColsByIdx (**args*)

Return the columns referenced by index (1,3,5)

getColsByName (**args*)

Return the columns referenced by label ('s','x','d')

getIndexes (*axis='all'*)

Return the matrix indexes ([rows],[cols]) where axis='row'/'col'/'all'

getLabels (*axis='all'*)

Return the matrix labels ([rows],[cols]) where axis='row'/'col'/'all'

getRowsByIdx (**args*)

Return the rows referenced by index (1,3,5)

getRowsByName (**args*)

Return the rows referenced by label ('s','x','d')

ridx = None

row = None

setByIdx (*row, col, val*)

setName (*row, col, val*)

setCol (*src*)

Assuming that the col index array is a permutation (full/subset) of a source label array by supplying that *src* to **setCol** maps the row labels to *cidx* and creates **self.col** (col label list)

setRow (*src*)

Assuming that the row index array is a permutation (full/subset) of a source label array by supplying that *src* to **setRow** it maps the row labels to *ridx* and creates **self.row** (row label list)

shape = None

PYSCESLINK

Interfaces to external software and API's, has replaced the PySCeS contrib classes.

class `pysces.PyscesLink.METATOOLlink` (*mod*, *__metatool_path__=None*)

New interface to METATOOL binaries

doEModes ()

Calculate the elementary modes by way of an interface to MetaTool.

METATOOL is a C program developed from 1998 to 2000 by Thomas Pfeiffer (Berlin) in cooperation with Stefan Schuster and Ferdinand Moldenhauer (Berlin) and Juan Carlos Nuno (Madrid). <http://www.biologie.hu-berlin.de/biophysics/Theory/tpfeiffer/metatool.html>

Arguments: None

getEModes ()

Returns the elementary modes as a linked list of fluxes

showEModes (*File=None*)

Print the results of an elementary mode analysis, generated with doEModes(), to screen or file.

Arguments: File [default=None]: Boolean, if True write parsed elementary modes to file

class `pysces.PyscesLink.SBWLayoutWebLink`

Enables access to DrawNetwork and SBMLLayout web services at www.sys-bio.org

DEBUGLEVEL = 1

DEBUGMODE = False

DRAWNETWORKLOADED = False

LAYOUTMODULELOADED = False

drawNetworkGetSBMLwithLayout ()

drawNetworkLoadSBML ()

getSBML ()

getSBMLlayout ()

```
getSVG ()
getVersion ()
layoutModuleGetSVG ()
layoutModuleLoadSBML ()
loadSBMLFileFromDisk (File, Dir=None)
loadSBMLFromString (str)
sbml = None
sbmllayout = None
sbwhost = '128.208.17.26'
setProxy (**kwargs)
    Set as many proxy settings as you need. You may supply a user name without a
    password in which case you will be prompted to enter one (once) when required
    (NO guarantees, implied or otherwise, on password security AT ALL). Arguments
    can be:
        user = 'daUser', pwd = 'daPassword', host = 'proxy.paranoid.net', port = 3128
svg = None
urlGET (host, urlpath)
urlPOST (host, urlpath, data)
class pysces.PyscesLink.SBWlink
    Generic access for local SBW services using SBWPython
    SBW_exposeAll (module)
    SBW_getActiveModules ()
    SBW_loadModule (module_name)
    moduleDict = None
    modules = None
    psbw = None
    sbw = None
    sbwModuleProxy = None
```

Part XI

Indices and tables

- `genindex`
- `modindex`
- `search`

p

`pysces.PyscesInterfaces`, 122

`pysces.PyscesLink`, 130

`pysces.PyscesModel`, 94

`pysces.PyscesPlot2`, 82

`pysces.PyscesScan`, 117

`pysces.PyscesStoich`, 124

`pysces.PyscesUtils`, 79

- add() (pysces.PyscesPlot2.FIFOBuffer method), 83
- addFormula() (pysces.PyscesModel.Function method), 96
- addModData() (pysces.PyscesModel.ScanDataObj method), 115
- addPoint() (pysces.PyscesModel.ScanDataObj method), 115
- addScanParameter() (pysces.PyscesScan.Scanner method), 121
- addUserOutput() (pysces.PyscesScan.Scanner method), 121
- ALL_VALID (pysces.PyscesModel.ScanDataObj attribute), 114
- analyseData() (pysces.PyscesScan.PITCONScanner method), 119
- AnalyseK() (pysces.PyscesStoich.Stoich method), 127
- AnalyseL() (pysces.PyscesStoich.Stoich method), 127
- Analyze() (pysces.PyscesScan.Scanner method), 120
- argsl (pysces.PyscesModel.Function attribute), 96
- array (pysces.PyscesStoich.StructMatrix attribute), 129
- array_kind (pysces.PyscesStoich.MathArrayFunc attribute), 126
- array_precision (pysces.PyscesStoich.MathArrayFunc attribute), 126
- array_type (pysces.PyscesStoich.MathArrayFunc attribute), 126
- assertRank2() (pysces.PyscesStoich.MathArrayFunc method), 126
- assignments (pysces.PyscesModel.Event attribute), 95
- axisInputStringToList() (pysces.PyscesPlot2.PlotBase method), 89
- BackSubstitution() (pysces.PyscesStoich.Stoich method), 127
- BagOfStuff (class in pysces.PyscesModel), 95
- castCopyAndTranspose() (pysces.PyscesStoich.MathArrayFunc method), 126
- chkmdir() (in module pysces.PyscesModel), 116
- chkpsec() (in module pysces.PyscesModel), 117
- cleanup (pysces.PyscesStoich.StructMatrix attribute), 129
- CleanNaNsFromArray() (pysces.PyscesModel.PysMod method), 100
- clone() (pysces.PyscesModel.PysMod method), 109
- closeAll() (pysces.PyscesPlot2.MatplotlibUPI method), 87
- closeAll() (pysces.PyscesPlot2.PyscesUPI method), 91
- closeScan() (pysces.PyscesModel.ScanDataObj method), 115
- code_string (pysces.PyscesModel.Event attribute), 95
- code_string (pysces.PyscesModel.EventAssignment attribute), 96
- code_string (pysces.PyscesModel.Function attribute), 96
- code_string (pysces.PyscesModel.PieceWise attribute), 99
- code_string (pysces.PyscesModel.ReactionObj attribute), 114

col	(pysces.PyscesModel.BagOfStuff	at-	CVODE_VPYTHON()
	tribute), 95		(pysces.PyscesModel.PysMod
col	(pysces.PyscesStoich.StructMatrix	at-	method), 99
	tribute), 129		
CommonStyleDefs			DATF_FORMAT
	(pysces.PyscesPlot2.GnuPlotUPI		(pysces.PyscesPlot2.GnuPlotUPI
	attribute), 83		attribute), 83
CommonStyleDefs			DEBUGLEVEL
	(pysces.PyscesPlot2.MatplotlibUPI		(pysces.PyscesLink.SBWLLayoutWebLink
	attribute), 87		attribute), 131
CommonStyleDefs			DEBUGMODE
	(pysces.PyscesPlot2.PlotBase	at-	(pysces.PyscesLink.SBWLLayoutWebLink
	tribute), 89		attribute), 131
commonType()			delay (pysces.PyscesModel.Event
	(pysces.PyscesStoich.MathArrayFunc		tribute), 95
	method), 126		doEigen() (pysces.PyscesModel.PysMod
compartment	(pysces.PyscesModel.ReactionObj		method), 109
	tribute), 114		doEigenMca() (pysces.PyscesModel.PysMod
ConvertFileD2U()	(in	module	method), 109
	pysces.PyscesUtils), 79		doEigenShow()
ConvertFileU2D()	(in	module	(pysces.PyscesModel.PysMod
	pysces.PyscesUtils), 79		method), 109
convertSBML2PSC()			doElas() (pysces.PyscesModel.PysMod
	(pysces.PyscesInterfaces.Core2interfaces		method), 109
	method), 123		doEModes() (pysces.PyscesLink.METATOOLink
CopyModels()	(in	module	method), 131
	pysces.PyscesUtils), 79		doLoad() (pysces.PyscesModel.PysMod
CopyTestModels()	(in	module	method), 109
	pysces.PyscesUtils), 79		doMca() (pysces.PyscesModel.PysMod
core	(pysces.PyscesInterfaces.Core2interfaces		method), 109
	tribute), 123		doMcaRC() (pysces.PyscesModel.PysMod
Core2interfaces	(class	in	method), 109
	pysces.PyscesInterfaces), 123		doMcaRCT() (pysces.PyscesModel.PysMod
core2psc	(pysces.PyscesInterfaces.Core2interfaces		method), 110
	tribute), 123		doSim() (pysces.PyscesModel.PysMod
core2sbml	(pysces.PyscesInterfaces.Core2interfaces		method), 110
	tribute), 123		doSimPerturb()
CVODE()	(pysces.PyscesModel.PysMod		(pysces.PyscesModel.PysMod
	method), 99		method), 110
CVODE_continue()			doSimPlot() (pysces.PyscesModel.PysMod
	(pysces.PyscesModel.PysMod		method), 110
	method), 99		doState() (pysces.PyscesModel.PysMod
CVODE_continuous_result			method), 110
	(pysces.PyscesModel.PysMod	at-	doStateShow() (pysces.PyscesModel.PysMod
	tribute), 100		method), 110
CVODE_EVENTS()			drawNetworkGetSBMLwithLayout()
	(pysces.PyscesModel.PysMod		(pysces.PyscesLink.SBWLLayoutWebLink
	method), 99		method), 131

- DRAWNETWORKLOADED (pysces.PyscesLink.SBWLLayoutWebLink attribute), 131
- drawNetworkLoadSBML() (pysces.PyscesLink.SBWLLayoutWebLink method), 131
- EvalCC() (pysces.PyscesModel.PysMod method), 100
- EvalEigen() (pysces.PyscesModel.PysMod method), 100
- EvalEpar() (pysces.PyscesModel.PysMod method), 100
- EvalEvar() (pysces.PyscesModel.PysMod method), 100
- EvalRC() (pysces.PyscesModel.PysMod method), 101
- EvalRCT() (pysces.PyscesModel.PysMod method), 101
- evaluateAssignment() (pysces.PyscesModel.EventAssignment method), 96
- Event (class in pysces.PyscesModel), 95
- EventAssignment (class in pysces.PyscesModel), 96
- export() (pysces.PyscesPlot2.GnuPlotUPI method), 83
- export() (pysces.PyscesPlot2.MatplotlibUPI method), 87
- export() (pysces.PyscesPlot2.PlotBase method), 89
- export() (pysces.PyscesPlot2.PyscesUPI method), 91
- exportArray2CSV() (pysces.PyscesUtils.WriteOutput method), 80
- exportArray2TXT() (pysces.PyscesUtils.WriteOutput method), 80
- exportLabelledArray() (pysces.PyscesUtils.WriteOutput method), 80
- exportLabelledArray2CSV() (pysces.PyscesUtils.WriteOutput method), 80
- exportLabelledArray2TXT() (pysces.PyscesUtils.WriteOutput method), 80
- exportLabelledArrayWithHeader() (pysces.PyscesUtils.WriteOutput method), 80
- exportLabelledArrayWithHeader2CSV() (pysces.PyscesUtils.WriteOutput method), 81
- exportLabelledArrayWithHeader2TXT() (pysces.PyscesUtils.WriteOutput method), 81
- exportLabelledLinkedList() (pysces.PyscesUtils.WriteOutput method), 81
- exportSimAsSedML() (pysces.PyscesModel.PysMod method), 111
- FIFOBuffer (class in pysces.PyscesPlot2), 83
- FINTSLV() (pysces.PyscesModel.PysMod method), 101
- Fix_S_fullinput() (pysces.PyscesModel.PysMod method), 101
- Fix_S_indinput() (pysces.PyscesModel.PysMod method), 101
- Fix_Sim() (pysces.PyscesModel.PysMod method), 101
- flux_labels (pysces.PyscesModel.ScanDataObj attribute), 115
- flux_labels (pysces.PyscesModel.StateDataObj attribute), 116
- fluxes (pysces.PyscesModel.ScanDataObj attribute), 115
- fluxes (pysces.PyscesModel.StateDataObj attribute), 116
- FluxGenSim() (pysces.PyscesModel.PysMod method), 101
- Forcing_Function() (pysces.PyscesModel.PysMod method), 101
- formula (pysces.PyscesModel.Event attribute), 95
- formula (pysces.PyscesModel.EventAssignment attribute), 96
- formula (pysces.PyscesModel.Function attribute), 96
- formula (pysces.PyscesModel.PieceWise attribute), 99

- formula (pysces.PyscesModel.ReactionObj attribute), 114
- Function (class in pysces.PyscesModel), 96
- functions (pysces.PyscesModel.Function attribute), 96
- g (pysces.PyscesPlot2.PyscesUPI attribute), 91
- g_file_write_array() (pysces.PyscesPlot2.GnuPlotUPI method), 83
- g_file_write_array3D() (pysces.PyscesPlot2.GnuPlotUPI method), 84
- g_pause() (pysces.PyscesPlot2.GnuPlotUPI method), 84
- g_write() (pysces.PyscesPlot2.GnuPlotUPI method), 84
- genOn (pysces.PyscesScan.Scanner attribute), 121
- get() (pysces.PyscesModel.BagOfStuff method), 95
- get() (pysces.PyscesModel.NewCoreBase method), 98
- get() (pysces.PyscesPlot2.FIFOBuffer method), 83
- getAllScanData() (pysces.PyscesModel.ScanDataObj method), 115
- getAllSimData() (pysces.PyscesModel.IntegrationDataObj method), 97
- getAllStateData() (pysces.PyscesModel.StateDataObj method), 116
- getArrayListAsArray() (pysces.PyscesScan.PITCONScanUtils method), 119
- getByIdx() (pysces.PyscesStoich.StructMatrix method), 129
- getByName() (pysces.PyscesStoich.StructMatrix method), 129
- getColsByIdx() (pysces.PyscesStoich.StructMatrix method), 129
- getColsByName() (pysces.PyscesStoich.StructMatrix method), 129
- getDataAtTime() (pysces.PyscesModel.IntegrationDataObj method), 97
- getDataInTimeInterval() (pysces.PyscesModel.IntegrationDataObj method), 97
- getEModes() (pysces.PyscesLink.METATOOLink method), 131
- getFluxes() (pysces.PyscesModel.ScanDataObj method), 115
- getFluxes() (pysces.PyscesModel.StateDataObj method), 116
- getIndexes() (pysces.PyscesStoich.StructMatrix method), 129
- getLabels() (pysces.PyscesStoich.StructMatrix method), 129
- getModData() (pysces.PyscesModel.ScanDataObj method), 115
- getName() (pysces.PyscesModel.NewCoreBase method), 98
- getOutput() (pysces.PyscesModel.IntegrationDataObj method), 97
- getOutput() (pysces.PyscesScan.Scanner method), 121
- getRates() (pysces.PyscesModel.IntegrationDataObj method), 97
- getResultMatrix() (pysces.PyscesScan.Scanner method), 121
- getRowsByIdx() (pysces.PyscesStoich.StructMatrix method), 129
- getRowsByName() (pysces.PyscesStoich.StructMatrix method), 129
- getRules() (pysces.PyscesModel.IntegrationDataObj method), 97
- getRules() (pysces.PyscesModel.ScanDataObj method), 115
- getRules() (pysces.PyscesModel.StateDataObj method), 116
- getSBML() (pysces.PyscesLink.SBWLLayoutWebLink method), 131
- getSBMLlayout() (pysces.PyscesLink.SBWLLayoutWebLink method), 131
- getScanData() (pysces.PyscesModel.ScanDataObj method), 115

method), 115

getSimData() (pysces.PyscesModel.IntegrationDataObj attribute), 116

method), 97

getSpecies() (pysces.PyscesModel.IntegrationDataObj (pysces.PyscesModel.ScanDataObj attribute), 114

method), 97

getSpecies() (pysces.PyscesModel.ScanDataObj HAS_SPECIES (pysces.PyscesModel.IntegrationDataObj attribute), 115

method), 115

getSpecies() (pysces.PyscesModel.StateDataObj attribute), 97

method), 116

getStateData() (pysces.PyscesModel.ScanDataObj (pysces.PyscesModel.StateDataObj attribute), 115

method), 116

getSVG() (pysces.PyscesLink.SBWLLayoutWebLink (pysces.PyscesModel.StateDataObj attribute), 116

method), 131

getTime() (pysces.PyscesModel.IntegrationDataObj HAS_STATE_OUTPUT (pysces.PyscesScan.Scanner attribute), 120

method), 98

GetUpperMatrix() (pysces.PyscesStoich.Stoich method), HAS_TIME (pysces.PyscesModel.IntegrationDataObj attribute), 97

127

GetUpperMatrixUsingQR() (pysces.PyscesStoich.Stoich method), HAS_USER_OUTPUT (pysces.PyscesScan.Scanner attribute), 120

127

getValue() (pysces.PyscesModel.NumberBase HAS_XDATA (pysces.PyscesModel.IntegrationDataObj attribute), 97

method), 99

getVersion() (pysces.PyscesLink.SBWLLayoutWebLink attribute), 97

method), 132

getXData() (pysces.PyscesModel.IntegrationDataObj (pysces.PyscesModel.ScanDataObj attribute), 115

method), 98

getXData() (pysces.PyscesModel.ScanDataObj HAS_XDATA (pysces.PyscesModel.StateDataObj attribute), 116

method), 115

getXData() (pysces.PyscesModel.StateDataObj attribute), 116

method), 116

GnuPlotUPI (class in pysces.PyscesPlot2), 83

hold() (pysces.PyscesPlot2.MatplotlibUPI method), 87

HAS_FLUXES (pysces.PyscesModel.ScanDataObj HYBRD() (pysces.PyscesModel.PysMod method), 102

attribute), 114

HAS_FLUXES (pysces.PyscesModel.StateDataObj info_moiety_conserve (pysces.PyscesStoich.Stoich attribute), 129

attribute), 115

HAS_MOD_DATA (pysces.PyscesModel.ScanDataObj InitialiseCompartments() (pysces.PyscesModel.PysMod method), 102

attribute), 114

HAS_RATES (pysces.PyscesModel.IntegrationDataObj InitialiseConservationArrays() (pysces.PyscesModel.PysMod method), 102

attribute), 97

HAS_RULES (pysces.PyscesModel.IntegrationDataObj InitialiseEvents() (pysces.PyscesModel.PysMod method), 102

attribute), 97

HAS_RULES (pysces.PyscesModel.ScanDataObj attribute), 114

InitialiseFunctions() (pysces.PyscesModel.PysMod method), 102
 InitialiseInputFile() (pysces.PyscesModel.PysMod method), 102
 InitialiseModel() (pysces.PyscesModel.PysMod method), 102
 InitialiseOldFunctions() (pysces.PyscesModel.PysMod method), 102
 InitialiseRuleChecks() (pysces.PyscesModel.PysMod method), 102
 InitialiseRules() (pysces.PyscesModel.PysMod method), 102
 IntegrationDataObj (class in pysces.PyscesModel), 97
 invalid_state_list (pysces.PyscesScan.Scanner attribute), 121
 invalid_state_list_idx (pysces.PyscesScan.Scanner attribute), 121
 invalid_states (pysces.PyscesModel.ScanDataObj attribute), 115
 IS_VALID (pysces.PyscesModel.IntegrationDataObj attribute), 97
 IS_VALID (pysces.PyscesModel.StateDataObj attribute), 116
 K_split_R() (pysces.PyscesStoich.Stoich method), 127
 L_split_R() (pysces.PyscesStoich.Stoich method), 128
 layoutModuleGetSVG() (pysces.PyscesLink.SBWLLayoutWebLink method), 132
 LAYOUTMODULELOADED (pysces.PyscesLink.SBWLLayoutWebLink attribute), 131
 layoutModuleLoadSBML() (pysces.PyscesLink.SBWLLayoutWebLink method), 132
 LinAlgError (pysces.PyscesStoich.MathArrayFunc attribute), 125
 list() (pysces.PyscesModel.BagOfStuff method), 95
 listAllOrdered() (pysces.PyscesModel.BagOfStuff method), 95
 load() (pysces.PyscesModel.BagOfStuff method), 95
 LoadFromFile() (pysces.PyscesModel.PysMod method), 102
 LoadFromString() (pysces.PyscesModel.PysMod method), 103
 loadSBMLFileFromDisk() (pysces.PyscesLink.SBWLLayoutWebLink method), 132
 loadSBMLFromString() (pysces.PyscesLink.SBWLLayoutWebLink method), 132
 LSODA() (pysces.PyscesModel.PysMod method), 102
 m (pysces.PyscesPlot2.PyscesUPI attribute), 91
 makeRange() (pysces.PyscesScan.Scanner method), 122
 MathArrayFunc (class in pysces.PyscesStoich), 125
 MatplotlibUPI (class in pysces.PyscesPlot2), 87
 matrix (pysces.PyscesModel.BagOfStuff attribute), 95
 MatrixFloatFix() (pysces.PyscesStoich.MathArrayFunc method), 125
 MatrixValueCompare() (pysces.PyscesStoich.MathArrayFunc method), 125
 MAX_OPEN_WINDOWS (pysces.PyscesPlot2.MatplotlibUPI attribute), 87
 METATOOLink (class in pysces.PyscesLink), 131
 mod (pysces.PyscesModel.Event attribute), 95
 mod (pysces.PyscesModel.EventAssignment attribute), 96
 mod (pysces.PyscesModel.Function attribute), 96

- mod (pysces.PyscesModel.ReactionObj attribute), 114
- mod_data (pysces.PyscesModel.ScanDataObj attribute), 115
- mod_data_labels (pysces.PyscesModel.ScanDataObj attribute), 115
- model (pysces.PyscesScan.PITCONScanUtils attribute), 119
- ModelLoad() (pysces.PyscesModel.PysMod method), 103
- moduleDict (pysces.PyscesLink.SBWlink attribute), 132
- modules (pysces.PyscesLink.SBWlink attribute), 132
- MSG_PRINT_INTERVAL (pysces.PyscesScan.Scanner attribute), 121
- name (pysces.PyscesModel.NewCoreBase attribute), 98
- name (pysces.PyscesModel.PieceWise attribute), 99
- nan_on_bad_state (pysces.PyscesScan.Scanner attribute), 122
- NewCoreBase (class in pysces.PyscesModel), 98
- NLEQ2() (pysces.PyscesModel.PysMod method), 103
- normal_timer() (pysces.PyscesUtils.TimerBox method), 79
- NumberBase (class in pysces.PyscesModel), 98
- OPEN (pysces.PyscesModel.ScanDataObj attribute), 115
- p_activateInterface() (pysces.PyscesPlot2.PyscesUPI method), 92
- p_deactivateInterface() (pysces.PyscesPlot2.PyscesUPI method), 92
- p_setInterface() (pysces.PyscesPlot2.PyscesUPI method), 92
- parameter_labels (pysces.PyscesModel.ScanDataObj attribute), 115
- parameters (pysces.PyscesModel.ScanDataObj attribute), 115
- ParGenSim() (pysces.PyscesModel.PysMod method), 103
- PAUSE_TIME (pysces.PyscesPlot2.GnuPlotUPI attribute), 83
- PieceWise (class in pysces.PyscesModel), 99
- piecewises (pysces.PyscesModel.Event attribute), 96
- piecewises (pysces.PyscesModel.EventAssignment attribute), 96
- piecewises (pysces.PyscesModel.Function attribute), 96
- piecewises (pysces.PyscesModel.ReactionObj attribute), 114
- PITCON() (pysces.PyscesModel.PysMod method), 103
- pitcon_range_high (pysces.PyscesScan.PITCONScanUtils attribute), 119
- pitcon_range_low (pysces.PyscesScan.PITCONScanUtils attribute), 119
- pitcon_res (pysces.PyscesScan.PITCONScanUtils attribute), 119
- pitcon_scan_density (pysces.PyscesScan.PITCONScanUtils attribute), 119
- pitcon_scan_parameter (pysces.PyscesScan.PITCONScanUtils attribute), 119
- pitcon_scan_parameter_3d (pysces.PyscesScan.PITCONScanUtils attribute), 119
- PITCONScanUtils (class in pysces.PyscesScan), 119
- PivotSort() (pysces.PyscesStoich.Stoich method), 128
- PivotSort_initial() (pysces.PyscesStoich.Stoich method), 128
- plot() (pysces.PyscesPlot2.GnuPlotUPI method), 84
- plot() (pysces.PyscesPlot2.MatplotlibUPI

- method), 87
- plot() (pysces.PyscesPlot2.PlotBase method), 89
- plot() (pysces.PyscesPlot2.PyscesUPI method), 92
- PlotBase (class in pysces.PyscesPlot2), 89
- plotLines() (pysces.PyscesPlot2.GnuPlotUPI method), 84
- plotLines() (pysces.PyscesPlot2.MatplotlibUPI method), 87
- plotLines() (pysces.PyscesPlot2.PlotBase method), 89
- plotLines() (pysces.PyscesPlot2.PyscesUPI method), 92
- PLUfactorize() (pysces.PyscesStoich.Stoich method), 128
- psbw (pysces.PyscesLink.SBWlink attribute), 132
- pyplot (pysces.PyscesPlot2.MatplotlibUPI attribute), 88
- pysces.PyscesInterfaces (module), 122
- pysces.PyscesLink (module), 130
- pysces.PyscesModel (module), 94
- pysces.PyscesPlot2 (module), 82
- pysces.PyscesScan (module), 117
- pysces.PyscesStoich (module), 124
- pysces.PyscesUtils (module), 79
- PyscesUPI (class in pysces.PyscesPlot2), 91
- PysMod (class in pysces.PyscesModel), 99
- quietRun (pysces.PyscesScan.Scanner attribute), 122
- rangeGen() (pysces.PyscesScan.Scanner method), 122
- rate (pysces.PyscesModel.ReactionObj attribute), 114
- rate_labels (pysces.PyscesModel.IntegrationDataObj attribute), 98
- rates (pysces.PyscesModel.IntegrationDataObj attribute), 98
- ReactionObj (class in pysces.PyscesModel), 114
- readMod2Core() (pysces.PyscesInterfaces.Core2interfaces method), 123
- readSBMLToCore() (pysces.PyscesInterfaces.Core2interfaces method), 123
- ReloadInitFunc() (pysces.PyscesModel.PysMod method), 103
- ReloadUserFunc() (pysces.PyscesModel.PysMod method), 103
- replot() (pysces.PyscesPlot2.GnuPlotUPI method), 84
- replot() (pysces.PyscesPlot2.PyscesUPI method), 92
- replotAndWait() (pysces.PyscesPlot2.GnuPlotUPI method), 84
- res_eigen (pysces.PyscesScan.PITCONScanUtils attribute), 119
- res_flux (pysces.PyscesScan.PITCONScanUtils attribute), 120
- res_idx (pysces.PyscesScan.PITCONScanUtils attribute), 120
- res_metab (pysces.PyscesScan.PITCONScanUtils attribute), 120
- res_user (pysces.PyscesScan.PITCONScanUtils attribute), 120
- reset() (pysces.PyscesModel.Event method), 96
- reset_step() (pysces.PyscesUtils.TimerBox method), 79
- resetInputParameters() (pysces.PyscesScan.Scanner method), 122
- ResetNumberFormat() (pysces.PyscesModel.PysMod method), 104
- ridx (pysces.PyscesStoich.StructMatrix attribute), 129
- row (pysces.PyscesModel.BagOfStuff attribute), 95
- row (pysces.PyscesStoich.StructMatrix attribute), 130
- rules (pysces.PyscesModel.IntegrationDataObj attribute), 98
- rules (pysces.PyscesModel.ScanDataObj attribute), 115
- rules (pysces.PyscesModel.StateDataObj attribute), 116
- rules_labels (pysces.PyscesModel.IntegrationDataObj attribute), 98
- rules_labels (pysces.PyscesModel.ScanDataObj attribute), 98

- attribute), 115
- rules_labels (pysces.PyscesModel.StateDataObj attribute), 116
- Run() (pysces.PyscesScan.Scanner method), 121
- RunAgain() (pysces.PyscesScan.Scanner method), 121
- runContinuation() (pysces.PyscesScan.PITCONScanUtils method), 120
- save() (pysces.PyscesPlot2.GnuPlotUPI method), 84
- save() (pysces.PyscesPlot2.MatplotlibUPI method), 88
- save() (pysces.PyscesPlot2.PlotBase method), 90
- save() (pysces.PyscesPlot2.PyscesUPI method), 92
- sbml (pysces.PyscesInterfaces.Core2interfaces attribute), 123
- sbml (pysces.PyscesLink.SBWLayoutWebLink attribute), 132
- sbml2core (pysces.PyscesInterfaces.Core2interfaces attribute), 123
- sbml_level (pysces.PyscesInterfaces.Core2interfaces attribute), 123
- sbml_version (pysces.PyscesInterfaces.Core2interfaces attribute), 123
- sbmllayout (pysces.PyscesLink.SBWLayoutWebLink attribute), 132
- sbw (pysces.PyscesLink.SBWlink attribute), 132
- SBW_exposeAll() (pysces.PyscesLink.SBWlink method), 132
- SBW_getActiveModules() (pysces.PyscesLink.SBWlink method), 132
- SBW_loadModule() (pysces.PyscesLink.SBWlink method), 132
- sbwhost (pysces.PyscesLink.SBWLayoutWebLink attribute), 132
- SBWLayoutWebLink (class in pysces.PyscesLink), 131
- SBWlink (class in pysces.PyscesLink), 132
- sbwModuleProxy (pysces.PyscesLink.SBWlink attribute), 132
- ScaleKL() (pysces.PyscesModel.PysMod method), 104
- ScalePivots() (pysces.PyscesStoich.Stoich method), 129
- scan (pysces.PyscesModel.PysMod attribute), 111
- Scan1() (pysces.PyscesModel.PysMod method), 104
- Scan1Plot() (pysces.PyscesModel.PysMod method), 104
- Scan2D() (pysces.PyscesModel.PysMod method), 104
- Scan2DPlot() (pysces.PyscesModel.PysMod method), 105
- ScanDataObj (class in pysces.PyscesModel), 114
- Scanner (class in pysces.PyscesScan), 120
- select() (pysces.PyscesModel.BagOfStuff method), 95
- SerialDecode() (pysces.PyscesModel.PysMod method), 105
- SerialEncode() (pysces.PyscesModel.PysMod method), 105
- set() (pysces.PyscesPlot2.GnuPlotUPI method), 85
- setArg() (pysces.PyscesModel.Function method), 96
- setAssignment() (pysces.PyscesModel.Event method), 96
- setAxisLabel() (pysces.PyscesPlot2.GnuPlotUPI method), 85
- setAxisLabel() (pysces.PyscesPlot2.MatplotlibUPI method), 88
- setAxisLabel() (pysces.PyscesPlot2.PlotBase method), 90
- setAxisLabel() (pysces.PyscesPlot2.PyscesUPI method), 92
- setByIdx() (pysces.PyscesStoich.StructMatrix method), 130
- setByName() (pysces.PyscesStoich.StructMatrix method), 130
- setCol() (pysces.PyscesStoich.StructMatrix method), 130

- setDataFileNumberFormat()
(pysces.PyscesPlot2.GnuPlotUPI
method), 85
- setFluxes() (pysces.PyscesModel.StateDataObj
method), 116
- setFormula() (pysces.PyscesModel.EventAssignment
method), 96
- setGraphTitle()
(pysces.PyscesPlot2.GnuPlotUPI
method), 85
- setGraphTitle()
(pysces.PyscesPlot2.MatplotlibUPI
method), 88
- setGraphTitle() (pysces.PyscesPlot2.PlotBase
method), 90
- setGraphTitle()
(pysces.PyscesPlot2.PyscesUPI
method), 93
- setGrid() (pysces.PyscesPlot2.GnuPlotUPI
method), 85
- setGrid() (pysces.PyscesPlot2.MatplotlibUPI
method), 88
- setGrid() (pysces.PyscesPlot2.PlotBase
method), 90
- setGrid() (pysces.PyscesPlot2.PyscesUPI
method), 93
- setKey() (pysces.PyscesPlot2.GnuPlotUPI
method), 85
- setKey() (pysces.PyscesPlot2.MatplotlibUPI
method), 88
- setKey() (pysces.PyscesPlot2.PlotBase
method), 90
- setKey() (pysces.PyscesPlot2.PyscesUPI
method), 93
- setKineticLaw()
(pysces.PyscesModel.ReactionObj
method), 114
- setLabels() (pysces.PyscesModel.IntegrationDataObj
method), 98
- setLabels() (pysces.PyscesModel.ScanDataObj
method), 115
- setLineWidth()
(pysces.PyscesPlot2.MatplotlibUPI
method), 88
- setLogScale() (pysces.PyscesPlot2.GnuPlotUPI
method), 85
- setLogScale() (pysces.PyscesPlot2.MatplotlibUPI
method), 88
- setLogScale() (pysces.PyscesPlot2.PlotBase
method), 90
- setLogScale() (pysces.PyscesPlot2.PyscesUPI
method), 93
- setLogScale() (pysces.PyscesPlot2.GnuPlotUPI
method), 93
- SetLoud() (pysces.PyscesModel.PysMod
method), 105
- setModValue() (pysces.PyscesScan.Scanner
method), 122
- setMultiplot() (pysces.PyscesPlot2.GnuPlotUPI
method), 85
- setName() (pysces.PyscesModel.NewCoreBase
method), 98
- setNoLogScale()
(pysces.PyscesPlot2.GnuPlotUPI
method), 85
- setNoLogScale()
(pysces.PyscesPlot2.MatplotlibUPI
method), 88
- setNoLogScale()
(pysces.PyscesPlot2.PlotBase
method), 90
- setNoLogScale()
(pysces.PyscesPlot2.PyscesUPI
method), 93
- setOrigin() (pysces.PyscesPlot2.GnuPlotUPI
method), 85
- setProxy() (pysces.PyscesLink.SBWLLayoutWebLink
method), 132
- SetQuiet() (pysces.PyscesModel.PysMod
method), 105
- setRange() (pysces.PyscesPlot2.GnuPlotUPI
method), 85
- setRange() (pysces.PyscesPlot2.MatplotlibUPI
method), 89
- setRange() (pysces.PyscesPlot2.PlotBase
method), 90
- setRange() (pysces.PyscesPlot2.PyscesUPI
method), 93
- setRates() (pysces.PyscesModel.IntegrationDataObj
method), 98
- setRow() (pysces.PyscesStoich.StructMatrix
method), 130
- setRules() (pysces.PyscesModel.IntegrationDataObj
method), 98
- setRules() (pysces.PyscesModel.StateDataObj
method), 116
- setSize() (pysces.PyscesPlot2.GnuPlotUPI
method), 86

- setSizeAndOrigin() (pysces.PyscesPlot2.GnuPlotUPI method), 86
- setSpecies() (pysces.PyscesModel.IntegrationDataObj method), 98
- setSpecies() (pysces.PyscesModel.StateDataObj method), 116
- SetStateSymb() (pysces.PyscesModel.PysMod method), 105
- setTerminal() (pysces.PyscesPlot2.GnuPlotUPI method), 86
- setTime() (pysces.PyscesModel.IntegrationDataObj method), 98
- setTrigger() (pysces.PyscesModel.Event method), 96
- setUserOuput() (pysces.PyscesScan.PITCONScanUtils method), 120
- setValue() (pysces.PyscesModel.NumberBase method), 99
- setVariable() (pysces.PyscesModel.EventAssignment method), 96
- setXData() (pysces.PyscesModel.IntegrationDataObj method), 98
- setXData() (pysces.PyscesModel.StateDataObj method), 116
- shape (pysces.PyscesStoich.StructMatrix attribute), 130
- showCC() (pysces.PyscesModel.PysMod method), 111
- showConserved() (pysces.PyscesModel.PysMod method), 111
- showEigen() (pysces.PyscesModel.PysMod method), 111
- showElas() (pysces.PyscesModel.PysMod method), 111
- showEModes() (pysces.PyscesLink.METATOOLink method), 131
- showEpar() (pysces.PyscesModel.PysMod method), 111
- showEvar() (pysces.PyscesModel.PysMod method), 112
- showFluxRelationships() (pysces.PyscesModel.PysMod method), 112
- showK() (pysces.PyscesModel.PysMod method), 112
- showL() (pysces.PyscesModel.PysMod method), 112
- showModel() (pysces.PyscesModel.PysMod method), 112
- showModifiers() (pysces.PyscesModel.PysMod method), 112
- showN() (pysces.PyscesModel.PysMod method), 112
- showNr() (pysces.PyscesModel.PysMod method), 113
- showODE() (pysces.PyscesModel.PysMod method), 113
- showODer() (pysces.PyscesModel.PysMod method), 113
- showPar() (pysces.PyscesModel.PysMod method), 113
- showRate() (pysces.PyscesModel.PysMod method), 113
- showRateEq() (pysces.PyscesModel.PysMod method), 113
- showSpecies() (pysces.PyscesModel.PysMod method), 113
- showSpeciesFixed() (pysces.PyscesModel.PysMod method), 114
- showSpeciesI() (pysces.PyscesModel.PysMod method), 114
- showState() (pysces.PyscesModel.PysMod method), 114
- SimPlot() (pysces.PyscesModel.PysMod method), 106
- Simulate() (pysces.PyscesModel.PysMod method), 106
- species (pysces.PyscesModel.IntegrationDataObj attribute), 98
- species (pysces.PyscesModel.ScanDataObj attribute), 115
- species (pysces.PyscesModel.StateDataObj attribute), 116
- species_labels (pysces.PyscesModel.IntegrationDataObj attribute), 98
- species_labels (pysces.PyscesModel.ScanDataObj attribute), 98

- attribute), 115
- species_labels
 - (pysces.PyscesModel.StateDataObj attribute), 116
- SplitLU() (pysces.PyscesStoich.Stoich method), 129
- splot() (pysces.PyscesPlot2.GnuPlotUPI method), 86
- splot() (pysces.PyscesPlot2.PlotBase method), 90
- splot() (pysces.PyscesPlot2.PyscesUPI method), 93
- splotSurfaces()
 - (pysces.PyscesPlot2.GnuPlotUPI method), 86
- splotSurfaces() (pysces.PyscesPlot2.PlotBase method), 91
- splotSurfaces()
 - (pysces.PyscesPlot2.PyscesUPI method), 93
- state (pysces.PyscesModel.Event attribute), 96
- State() (pysces.PyscesModel.PysMod method), 106
- state0 (pysces.PyscesModel.Event attribute), 96
- StateDataObj (class in pysces.PyscesModel), 115
- step_timer() (pysces.PyscesUtils.TimerBox method), 79
- stepGen() (pysces.PyscesScan.Scanner method), 122
- Stoich (class in pysces.PyscesStoich), 127
- Stoich_nmatrix_SetValue()
 - (pysces.PyscesModel.PysMod method), 107
- Stoichiometry_Analyse()
 - (pysces.PyscesModel.PysMod method), 107
- Stoichiometry_Init()
 - (pysces.PyscesModel.PysMod method), 107
- Stoichiometry_Load_Serial()
 - (pysces.PyscesModel.PysMod method), 107
- Stoichiometry_ReAnalyse()
 - (pysces.PyscesModel.PysMod method), 107
- Stoichiometry_Save_Serial()
 - (pysces.PyscesModel.PysMod method), 107
- stop() (pysces.PyscesUtils.TimerBox method), 79
- StoreData() (pysces.PyscesScan.Scanner method), 121
- str2bool() (in module pysces.PyscesUtils), 81
- StructMatrix (class in pysces.PyscesStoich), 129
- SVD_Rank_Check()
 - (pysces.PyscesStoich.Stoich method), 128
- svg (pysces.PyscesLink.SBWLayoutWebLink attribute), 132
- SwapCol() (pysces.PyscesStoich.MathArrayFunc method), 125
- SwapCold() (pysces.PyscesStoich.MathArrayFunc method), 125
- SwapColz() (pysces.PyscesStoich.MathArrayFunc method), 125
- SwapElem() (pysces.PyscesStoich.MathArrayFunc method), 126
- SwapRow() (pysces.PyscesStoich.MathArrayFunc method), 126
- SwapRowd() (pysces.PyscesStoich.MathArrayFunc method), 126
- SwapRowz() (pysces.PyscesStoich.MathArrayFunc method), 126
- symbols (pysces.PyscesModel.Event attribute), 96
- symbols (pysces.PyscesModel.EventAssignment attribute), 96
- symbols (pysces.PyscesModel.Function attribute), 96
- symbols (pysces.PyscesModel.ReactionObj attribute), 114
- Terminals (pysces.PyscesPlot2.GnuPlotUPI attribute), 83
- testInputParameter()
 - (pysces.PyscesScan.Scanner method), 122
- TestSimState() (pysces.PyscesModel.PysMod method), 108
- time (pysces.PyscesModel.IntegrationDataObj attribute), 98
- time_label (pysces.PyscesModel.IntegrationDataObj attribute), 98

- timer (pysces.PyscesScan.PITCONScanUtils writeCore2PSC()
attribute), 120 (pysces.PyscesInterfaces.Core2interfaces
method), 123
- TimerBox (class in pysces.PyscesUtils), 79
- trigger (pysces.PyscesModel.Event attribute), writeCore2SBML()
96 (pysces.PyscesInterfaces.Core2interfaces
method), 124
- TYPE_INFO (pysces.PyscesModel.IntegrationDataObj writeMod2PSC()
attribute), 97 (pysces.PyscesInterfaces.Core2interfaces
method), 124
- unset() (pysces.PyscesPlot2.GnuPlotUPI writeMod2SBML()
method), 87 (pysces.PyscesInterfaces.Core2interfaces
method), 124
- unsetMultiplot() writeMod2SBML()
(pysces.PyscesPlot2.GnuPlotUPI (pysces.PyscesInterfaces.Core2interfaces
method), 87 method), 124
- urlGET() (pysces.PyscesLink.SBWLayoutWebLink WriteOutput (class in pysces.PyscesUtils), 80
method), 132
- urlPOST() (pysces.PyscesLink.SBWLayoutWebLink xcode (pysces.PyscesModel.Event attribute),
method), 132 96
- USE_QR (pysces.PyscesStoich.Stoich at- xcode (pysces.PyscesModel.EventAssignment
tribute), 129 attribute), 96
- User_Function() xcode (pysces.PyscesModel.Function at-
(pysces.PyscesModel.PysMod tribute), 97
method), 108 xcode (pysces.PyscesModel.PieceWise
attribute), 99
- user_output (pysces.PyscesScan.PITCONScanUtils xcode (pysces.PyscesModel.ReactionObj at-
attribute), 120 tribute), 114
- value (pysces.PyscesModel.Function at- xdata (pysces.PyscesModel.IntegrationDataObj
tribute), 97 attribute), 98
- value (pysces.PyscesModel.NumberBase at- xdata (pysces.PyscesModel.ScanDataObj at-
tribute), 99 tribute), 115
- value (pysces.PyscesModel.PieceWise at- xdata (pysces.PyscesModel.StateDataObj at-
tribute), 99 tribute), 116
- value_initial (pysces.PyscesModel.NumberBase xdata_labels (pysces.PyscesModel.IntegrationDataObj
attribute), 99 attribute), 98
- variable (pysces.PyscesModel.EventAssignment xdata_labels (pysces.PyscesModel.ScanDataObj
attribute), 96 attribute), 115
- VersionCheck() (in module xdata_labels (pysces.PyscesModel.StateDataObj
pysces.PyscesUtils), 79 attribute), 116
- wait() (pysces.PyscesPlot2.PlotBase method),
91
- WasteManagement (class in
pysces.PyscesModel), 116
- Write_array() (pysces.PyscesModel.PysMod
method), 108
- Write_array_html()
(pysces.PyscesModel.PysMod
method), 108
- Write_array_latex()
(pysces.PyscesModel.PysMod
method), 108